FASTROAD AR 2



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Glacier Silver
RAHMEN	ALUXX-grade aluminum, 12x142mm thru-axle, disc
GABEL	Advanced-grade composite, composite OverDrive steerer, 12x100mm thru-axle, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Sport Flat, 31.8 XS:64cm, S:64cm, M:68cm, M/L: 68cm, L:68cm, XL:68cm
GRIFFE	Giant ErgoContact
VORBAU	Giant Sports XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SATTELSTÜTZE	Giant D-Fuse, alloy, 350mm
SATTEL	Giant ErgoContact
PEDALE	platform pedal
ANTRIEB	
SCHALTHEBEL	Shimano CUES U4000, 9-speed
UMWERFER	N/A
SCHALTWERK	Shimano CUES
BREMSEN	Tektro HD-R280, Giant MPH rotors [F]160mm, [R]160mm
BREMSHEBEL	Tektro HD-R280
KASSETTE	Shimano CS-LG3009, 11x41
KETTE	Shimano CN-LG500
KURBEL	FSA Omega AGX+, 42t XS:170mm, S:170mm, M:170mm, M/L:172.5mm, L:172.5mm, XL: 175mm
TRETLAGER	threaded

LAUFRÄDER	
FELGEN	Giant S-X2 Disc wheelset
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Maxxis Re-Fuse, tubeless, 700x40c
EXTRAS	tubeless prepared, 42mm max tire size
LIMITS	
MAX TIRE CLEARANCE	42mm

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	435	455	475	495	525	555
Sitzrohrwinkel	73.5°	73.5°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	545	560	575	590	610	630
Steuerrohr-Länge (mm)	110	130	155	175	200	225
Steuerrohr-Winkel	70.5°	70.5°	71.0°	71.0°	71.5°	71.5°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	73.7	73.7	70.4	70.4	67.1	67.1
Radstand (mm)	1031	1047	1058	1069	1084	1105
Kettenstreben-Länge (mm)	435	435	435	435	435	435
Tretlager-Höhe (mm)	75	75	75	75	75	75
Stack (mm)	533	552	578	597	623	646
Reach (mm)	387	396	404	407	419	432
Überstandshöhe (mm)	718	736	756	773	800	826
Lenkerbreite (mm)	640	640	680	680	680	680
Vorbaulänge (mm)	70	80	90	90	100	110
Kurbellänge (mm)	170	170	170	172.5	172.5	172.5
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.