



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Dark Jungle
RAHMEN	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
GABEL	Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset
DÄMPFER	Fox Float SL Performance, 210/50
KOMPONENTEN	
LENKER	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIFFE	Giant Tactal, lock on
VORBAU	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
SATTELSTÜTZE	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SATTEL	Giant Grit
PEDALE	platform [GC,GT]
ANTRIEB	
SCHALTHEBEL	SRAM Eagle 90 mechanical, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM Eagle 90 Transmission
BREMSEN	Shimano SLX BR-M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BREMSHEBEL	Shimano SLX BL-M7100
KASSETTE	SRAM 70 1270, 10x52
KETTE	SRAM 90 Transmission
KURBEL	SRAM 90 Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant XCA WheelSystem
NABE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPEICHEN	Sapim
REIFEN	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIEDATEN

RAHMEN	S		M		L		XL	
	LOW HIGH		LOW HIGH		LOW HIGH		LOW HIGH	
Sitzrohlrlänge (mm)	400		420		465		495	
Sitzrohrwinkel	75.0° 75.5°		75.1° 75.5°		75.1° 75.6°		75.1° 75.6°	
Oberrohrlänge (mm)	577 575		603 602		625 624		653 651	
Steuerrohr-Länge (mm)	90		95		105		115	
Steuerrohr-Winkel	66.0° 66.5°		66.1° 66.5°		66.1° 66.6°		66.1° 66.6°	
Gabelneigung (mm)	44		44		44		44	
Trail (mm)	119.5 115.7		119.3 115.6		119.2 115.5		119 115.4	
Radstand (mm)	1145 1144		1172 1171		1196 1195		1225 1224	
Kettenstreben-Länge (mm)	437 435		437 435		437 435		437 435	
Tretlager-Höhe (mm)	48 42		48 42		48 42		48 42	
Stack (mm)	606 602		611 607		620 616		629 625	
Reach (mm)	415 420		440 445		460 465		485 490	
Überstandshöhe (mm)	774 780		770 776		762 769		757 764	
Lenkerbreite (mm)	780		780		780		780	
Vorbaulänge (mm)	50		50		60		70	
Kurbellänge (mm)	170		170		175		175	

Spezifikations-, Preis- und Farbänderungen vorbehalten.