



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Carbon/Moon Dust
RAHMEN	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
GABEL	Fox 34 Rhythm, 130mm, GRIP damper, Boost 15x110, 44mm offset
DÄMPFER	Fox Float SL Performance, 210/50
KOMPONENTEN	
LENKER	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIFFE	Giant Tactal, lock on
VORBAU	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
SATTELSTÜTZE	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SATTEL	Giant Grit Core
PEDALE	platform [GC,GT]
ANTRIEB	
SCHALTHEBEL	Shimano Deore mechanical, 1x12
UMWERFER	N/A
SCHALTWERK	Shimano Deore
BREMSSEN	TRP Slate EVO hydraulic, stainless, 6-bolt rotors [F]203mm, [R]180mm
BREMSHEBEL	TRP Slate EVO
KASSETTE	Shimano M6100, 10x51
KETTE	KMC X-12
KURBEL	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
TRETLAGER	Praxis, press fit

LAUFRÄDER	
FELGEN	Giant XCA WheelSystem
NABE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPEICHEN	Sapim
REIFEN	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohrlänge (mm)	400	420	465	495
Sitzrohrwinkel	75.0° 75.5°	75.1° 75.5°	75.1° 75.6°	75.1° 75.6°
Oberrohrlänge (mm)	577 575	603 602	625 624	653 651
Steuerrohr-Länge (mm)	90	95	105	115
Steuerrohr-Winkel	66.0° 66.5°	66.1° 66.5°	66.1° 66.6°	66.1° 66.6°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	119.5 115.7	119.3 115.6	119.2 115.5	119 115.4
Radstand (mm)	1145 1144	1172 1171	1196 1195	1225 1224
Kettenstreben-Länge (mm)	437 435	437 435	437 435	437 435
Tretlager-Höhe (mm)	48 42	48 42	48 42	48 42
Stack (mm)	606 602	611 607	620 616	629 625
Reach (mm)	415 420	440 445	460 465	485 490
Überstandshöhe (mm)	774 780	770 776	762 769	757 764
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	50	50	60	70
Kurbellänge (mm)	170	170	175	175

Spezifikations-, Preis- und Farbänderungen vorbehalten.