

ANTHEM X ADVANCED SL FRAME

GIANT



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Pixel Pulse
RAHMEN	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
GABEL	N/A
DÄMPFER	Fox Float SL Factory, 210/50
KOMPONENTEN	
LENKER	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
VORBAU	Giant Integrated XC, alloy S:50mm, M:50mm, L:60mm, XL:70mm
SATTELSTÜTZE	N/A

LAUFRÄDER	
EXTRAS	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohlänge (mm)	400	420	465	495
Sitzrohrwinkel	75.0° 75.5°	75.1° 75.5°	75.1° 75.6°	75.1° 75.6°
Oberrohrlänge (mm)	577 575	603 602	625 624	653 651
Steuerrohr-Länge (mm)	90	95	105	115
Steuerrohr-Winkel	66.0° 66.5°	66.1° 66.5°	66.1° 66.6°	66.1° 66.6°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	119.5 115.7	119.3 115.6	119.2 115.5	119 115.4
Radstand (mm)	1145 1144	1172 1171	1196 1195	1225 1224
Kettenstreben-Länge (mm)	437 435	437 435	437 435	437 435
Tretlager-Höhe (mm)	48 42	48 42	48 42	48 42
Stack (mm)	606 602	611 607	620 616	629 625
Reach (mm)	415 420	440 445	460 465	485 490
Überstandshöhe (mm)	774 780	770 776	762 769	757 764
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	50	50	60	70
Kurbellänge (mm)	170	170	175	175

Spezifikations-, Preis- und Farbänderungen vorbehalten.