



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Abyss Black
RAHMEN	ALUXX-grade aluminum, 12x142mm thru-axle, disc
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant D-Fuse SL XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIFFE	Velo cork tape with gel
VORBAU	Giant Contact XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SATTELSTÜTZE	Giant D-Fuse, composite, 14mm offset
SATTEL	Giant Approach
ANTRIEB	
SCHALTHEBEL	Shimano 105
UMWERFER	Shimano 105
SCHALTWERK	Shimano 105 GS
BREMSEN	Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano 105
KASSETTE	Shimano 105, 12-speed, 11x36
KETTE	KMC X12L-1
KURBEL	Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
TRETLAGER	Shimano BB-RS501

LAUFRÄDER	
FELGEN	Giant P-R2 Disc wheelset, alloy, [F]25mm, [R]25mm
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Giant Gavia Fondo 2, tubeless, 700x32c (34mm)
EXTRAS	fender mount, tubeless prepared, 38mm max tire size
LIMITS	
MAX TIRE CLEARANCE	38mm

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	430	465	500	535	555	585
Sitzrohrwinkel	75.0°	74.0°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	515	535	550	565	580	595
Steuerrohr-Länge (mm)	115	135	150	170	190	215
Steuerrohr-Winkel	71.5°	71.8°	72.0°	72.5°	72.5°	72.5°
Gabelneigung (mm)	53	53	53	53	53	53
Trail (mm)	62.9	61.3	59.6	56.4	56.4	56.4
Radstand (mm)	994	1003	1011	1015	1031	1046
Kettenstreben-Länge (mm)	422	422	422	422	422	422
Tretlager-Höhe (mm)	80	80	80	80	80	80
Stack (mm)	539	559	574	595	614	638
Reach (mm)	371	375	380	383	392	400
Überstandshöhe (mm)	727	759	783	810	829	856
Lenkerbreite (mm)	400	400	420	420	440	440
Vorbaulänge (mm)	80	90	100	100	110	110
Kurbellänge (mm)	165	165	170	170	172.5	172.5

Spezifikations-, Preis- und Farbänderungen vorbehalten.