



Spezifikationen

Rahmen	
Größen	XS, S, M, M/L, L, XL
Farbe	Meteorite Mist
Rahmen	Advanced-grade Composite, 12x142mm thru-axle, disc
Gabel	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
Komponenten	
Lenker	Giant Contact SL D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
Griffe	Stratus Lite 3.0
Vorbau	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
Sattelstütze	Giant D-Fuse, composite, 14mm offset
Sattel	Giant Approach
Antrieb	
Schalthebel	Shimano 105 Di2
Umwerfer	Shimano 105 Di2
Schaltwerk	Shimano 105 Di2
Bremsen	Shimano 105 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]160mm
Bremshebel	Shimano 105 Di2
Kassette	Shimano 105, 12-speed, 11x36
Kette	KMC X12L-1
Kurbel	Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
Tretlager	Shimano, press fit

Laufräder	
Felgen	Giant SLR 2 40 Carbon Disc WheelSystem
Nabe	[F] Giant Alloy Hub, CenterLock, 12mm thru-axle, [R] Giant Alloy Hub, 3-pawl driver, CenterLock, 12mm thru-axle
Speichen	Sapim
Reifen	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
Extras	tubeless prepared, 40mm max tire size
Limits	
Max Tire Clearance	40mm

Geometriedaten

Rahmen	XS	S	M	ML	L	XL
Sitzrohlrlänge (mm)	410	445	480	515	535	565
Sitzrohrwinkel	74.5°	74.0°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	515	530	545	560	575	595
Steuerrohr-Länge (mm)	125	135	150	175	195	215
Steuerrohr-Winkel	70.5°	71.8°	72.5°	72.5°	72.5°	72.5°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	71.6	63.4	58.6	58.6	58.6	58.6
Radstand (mm)	995	994	998	1010	1025	1040
Kettenstreben-Länge (mm)	420	420	420	420	420	420
Tretlager-Höhe (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Überstandshöhe (mm)	705	733	762	796	814	841
Lenkerbreite (mm)	410	410	430	430	450	450
Vorbaulänge (mm)	80	90	100	100	110	110
Kurbellänge (mm)	165	165	170	170	172.5	172.5

Spezifikations-, Preis- und Farbänderungen vorbehalten.