

DEFY ADVANCED E+ ELITE 2



Spezifikationen

Hybrid Cycling Technology	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
SENSOR	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
AKKU	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
Rahmen	
GRÖSSEN	S, M, ML, L, XL
FARBE	Meteor Storm
RAHMEN	Advanced-grade composite, 12x145 thru-axle
GABEL	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
Komponenten	
LENKER	Giant Contact SL D-Fuse 31.8 alloy
VORBAU	Contact SL Aerolight 31.8 alloy
SATTELSTÜTZE	Giant D-Fuse, Composite, 14mm offset
SATTEL	Giant Approach
Antrieb	
SCHALTHEBEL	Sram Rival AXS
UMWERFER	Sram Rival AXS
SCHALTWERK	Sram Rival AXS
BREMSSEN	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
BREMSHEBEL	Sram Rival AXS HRD
KASSETTE	Sram Rival XG-1250 10x36T 12-speed
KETTE	Sram Rival 12-speed
KURBEL	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS
TRETLAGER	Giant E+ System BB55

Laufräder	
FELGEN	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
REIFEN	Giant Gavia Fondo 0, tubeless, 700x32, folding
EXTRAS	Fender adapter
Accessories	
BELEUCHTUNG	Seatpost clamp integrated tail light

Geometriedaten

Rahmen	S	M	ML	L	XL
Sitzrohlrlänge (mm)	445	480	515	535	565
Sitzrohrwinkel	74.0°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	530	545	560	575	590
Steuerrohr-Länge (mm)	130	145	167	187	205
Steuerrohr-Winkel	71.5°	72.5°	72.5°	72.5°	72.5°
Gabelneigung (mm)	50	50	50	50	50
Radstand (mm)	994	995	1008	1023	1037.9
Kettenstreben-Länge (mm)	420	420	420	420	420
Tretlager-Höhe (mm)	80	80	75	75	75
Stack (mm)	542	560	576	595	612.4
Reach (mm)	374	379	384	393	402.6
Überstandshöhe (mm)	716	746	779	799	824
Lenkerbreite (mm)	400	420	420	440	440
Vorbaulänge (mm)	90	100	110	110	120
Radgrösse	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.