



SPEZIFIKATIONEN

| HYBRID CYCLING TECHNOLOGY |                                                                                                         |
|---------------------------|---------------------------------------------------------------------------------------------------------|
| MOTOR                     | Giant SyncDrive Pro 2 85Nm PedalPlus 6-Sensor technology                                                |
| SENSOR                    | Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels                                 |
| DISPLAY                   | Giant RideControl Dash 2, high-angle visibility, full color LCD display                                 |
| AKKU                      | Giant EnergyPak Smart 750Wh                                                                             |
| CHARGER                   | Giant EnergyPak smart charger 4A                                                                        |
| CONNECTIVITY              | Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile                         |
| RAHMEN                    |                                                                                                         |
| GRÖSSEN                   | S, M, L, XL, XXL                                                                                        |
| FARBE                     | Deep Lake                                                                                               |
| RAHMEN                    | ALUXX aluminum, Overdrive 1.125" - 1.8" head tube, 148x12mm Thru-axle, integrated KSA40 kickstand mount |
| GABEL                     | SR Suntour XCR34 2CR coil boost 130mm travel 15x110mm AH axle                                           |
| DÄMPFER                   | -                                                                                                       |
| KOMponenten               |                                                                                                         |
| LENKER                    | Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]                                                    |
| GRIFFE                    | Giant Sole-O                                                                                            |
| VORBAU                    | Giant Contact                                                                                           |
| SATTELSTÜTZE              | Giant Contact Switch Core dropper seatpost, 100mm travel                                                |
| SATTEL                    | Giant Ergo Contact Trail, ESG                                                                           |
| PEDALE                    | Anti-slip Platform                                                                                      |
| ANTRIEB                   |                                                                                                         |
| SCHALTHEBEL               | Shimano Cues                                                                                            |
| SCHALTWERK                | Shimano Cues 10-speed                                                                                   |
| BREMSen                   | Shimano MT200, hydraulic disc, 180mm [F/R]                                                              |
| BREMSHEBEL                | Shimano BL-MT200                                                                                        |
| KASSETTE                  | Shimano Cues11-48T 10-speed                                                                             |
| KETTE                     | Shimano Linkglide CN-LG500                                                                              |
| KURBEL                    | Forged allumin direct-mount chainring steel 36T, Forged alumium crank arms                              |

| LAUFRÄDER    |                                                          |
|--------------|----------------------------------------------------------|
| FELGEN       | Giant XCT 29 Tubeless Ready 25mm e-bike optimized        |
| NABE         | eTracker boost alloy 6-bolt disc 15x110mm[F] 12x148mm[R] |
| SPEICHEN     | Stainless steel                                          |
| REIFEN       | Maxxis Rekon 29x2.4", EXO, 60TPI                         |
| ACCESSORIES  |                                                          |
| BELEUCHTUNG  | -                                                        |
| SCHLOSS      | ABUS Xplus battery lock                                  |
| GEPÄCKTRÄGER | -                                                        |

GEOMETRIEDATEN

| RAHMEN                   | S     | M     | L     | XL    | XXL   |
|--------------------------|-------|-------|-------|-------|-------|
| Sitzrohrlänge (mm)       | 380   | 420   | 460   | 495   | 530   |
| Sitzrohrwinkel           | 75.0° | 75.0° | 75.0° | 75.0° | 75.0° |
| Oberrohrlänge (mm)       | 590   | 610   | 630   | 650   | 670   |
| Steuerrohr-Länge (mm)    | 110   | 120   | 130   | 140   | 150   |
| Steuerrohr-Winkel        | 66.0° | 66.0° | 66.0° | 66.0° | 66.0° |
| Gabelneigung (mm)        | 51    | 51    | 51    | 51    | 51    |
| Radstand (mm)            | 1197  | 1219  | 1241  | 1262  | 1284  |
| Kettenstreben-Länge (mm) | 470   | 470   | 470   | 470   | 470   |
| Tretlager-Höhe (mm)      | 65    | 65    | 65    | 65    | 65    |
| Stack (mm)               | 647   | 656   | 665   | 674   | 684   |
| Reach (mm)               | 416   | 434   | 451   | 469   | 486   |
| Lenkerbreite (mm)        | 750   | 780   | 780   | 780   | 780   |
| Vorbaulänge (mm)         | 40    | 40    | 50    | 50    | 50    |
| Radgrösse                | 29"   | 29"   | 29"   | 29"   | 29"   |

Spezifikations-, Preis- und Farbänderungen vorbehalten.