



CARACTÉRISTIQUES TECHNIQUES

TECHNOLOGIE HYBRID	
MOTOR	Giant SyncDrive Pro 2 85Nm PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATTERIE	Giant EnergyPak Smart 750Wh
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
CADRE	
TAILLES	S, M, L, XL, XXL
COLORIS	Good Grey
CADRE	ALUXX aluminum, Overdrive 1.125" - 1.8" head tube, 148x12mm Thru-axle, integrated KSA40 kickstand mount
FOURCHE	SR Suntour XCR34 2CR coil boost 130mm travel 15x110mm AH axle
AMORTISSEUR	-
COMPOSANTS	
CINTRE	Giant Connect TR Riser 31.8x750mm [S], 780mm [M-XXL]
POIGNÉES	Giant Sole-O
POTENCE	Giant Contact
TIGE DE SELLE	Giant Contact Switch Core dropper seatpost, 100mm travel
SELLE	Giant Ergo Contact Trail, ESG
PÉDALES	Anti-slip Platform
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano Cues
DÉRAILLEUR ARRIÈRE	Shimano Cues 10-speed
FREINS	Shimano MT200, hydraulic disc, 180mm [F/R]
LEVIER DE FREIN	Shimano BL-MT200
CASSETTE	Shimano Cues11-48T 10-speed
CHAÎNE	Shimano Linkglide CN-LG500
PÉDALIER	Forged allumin direct-mount chainring steel 36T, Forged alumium crank arms

ROUES	
JANTES	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
MOYEUX	eTracker boost alloy 6-bolt disc 15x110mm[F] 12x148mm[R]
RAYONS	Stainless steel
PNEUS	Maxxis Rekon 29x2.4", EXO, 60TPI
ACCESSOIRES	
ÉCLAIRAGE	Giant Recon EL50 Axa BlueLine Steady E6 rear
ANTI-VOL	ABUS Xplus battery lock
CARRIER	Giant Rack-It MIK

GÉOMÉTRIE

CADRE	S	M	L	XL	XXL
Longueur de tube de selle (mm)	380	420	460	495	530
Angle de tube de selle	75,0°	75,0°	75,0°	75,0°	75,0°
Longueur du tube supérieur (mm)	590	610	630	650	670
Longueur du tube de direction (mm)	110	120	130	140	150
Angle du tube de direction	66,0°	66,0°	66,0°	66,0°	66,0°
Déport de fourche (mm)	51	51	51	51	51
Empattement (mm)	1197	1219	1241	1262	1284
Longueur des bases (mm)	470	470	470	470	470
Hauteur du boîtier de pédalier (mm)	65	65	65	65	65
Stack (mm)	647	656	665	674	684
Reach (mm)	416	434	451	469	486
Largeur de cintre (mm)	750	780	780	780	780
Longueur de potence (mm)	40	40	50	50	50
Diamètre des roues	29"	29"	29"	29"	29"

Giant Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.