



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Mercury/Raw Carbon
RAHMEN	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
GABEL	Fox 38 Factory, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset
DÄMPFER	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Contact TR35, 800x35mm, 35mm rise
GRIFFE	Giant Tactal Pro Single
VORBAU	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SATTELSTÜTZE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SATTEL	Giant Romero SL
ANTRIEB	
SCHALTHEBEL	SRAM AXS Pod, discrete clamp, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM GX Eagle Transmission
BREMSEN	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
BREMSHEBEL	TRP DH-R EVO, hydraulic
KASSETTE	SRAM GX Eagle Transmission, 10x52
KETTE	SRAM GX Eagle Transmission
KURBEL	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NABE	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
SPEICHEN	Sapim, 28, straight pull, DBL Technology
REIFEN	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRIEDATEN

RAHMEN	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sitzrohrlänge (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Sitzrohrwinkel	77.5° 77.8° 78.2°			77.5° 77.8° 78.2°			76.5° 76.9° 77.2°			76.5° 76.9° 77.2°		
Oberrohrlänge (mm)	558 557 556			589 588 587			622 621 621			654 653 653		
Steuerrohr-Länge (mm)	100			105			115			120		
Steuerrohr-Winkel	62.7° 63.0° 63.4°			62.7° 63.0° 63.4°			62.7° 63.1° 63.4°			62.7° 63.1° 63.4°		
Gabelneigung (mm)	44			44			44			44		
Trail (mm)	147 144 141			147 144 141			147 144 141			147 144 141		
Radstand (mm)	1214 1213 1212			1246 1245 1244			1271 1270 1269			1304 1303 1302		
Kettenstreben-Länge (mm)	445 443 442			445 443 442			445 443 442			445 443 442		
Tretlager-Höhe (mm)	29 24 19			29 24 19			29 24 19			29 24 19		
Stack (mm)	633 630 627			638 635 632			647 644 641			652 649 646		
Reach (mm)	418 421 426			448 452 456			468 471 476			499 503 507		
Überstandshöhe (mm)	714 718 723			733 738 742			746 750 755			762 766 771		
Lenkerbreite (mm)	800			800			800			800		
Vorbaulänge (mm)	40			40			40			40		
Kurbellänge (mm)	165			170			170			170		
Radgrösse	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

Spezifikations-, Preis- und Farbänderungen vorbehalten.