



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Mercury/Raw Carbon
CADRE	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
FOURCHE	Fox 38 Factory, 170mm, GRIP X2 damper, 15x110 Kabolt X, 44mm offset
AMORTISSEUR	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact TR35, 800x35mm, 35mm rise
POIGNÉES	Giant Tactal Pro Single
POTENCE	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
TIGE DE SELLE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SELLE	Giant Romero SL
DÉRAILLEUR	
MANETTES DÉRAILLEUR	SRAM AXS Pod, discrete clamp, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	SRAM GX Eagle Transmission
FREINS	TRP EVO DH-R, hydraulic, TRP rotors [F]220mm, [R]200mm
LEVIER DE FREIN	TRP DH-R EVO, hydraulic
CASSETTE	SRAM GX Eagle Transmission, 10x52
CHAÎNE	SRAM GX Eagle Transmission
PÉDALIER	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
MOYEUX	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
RAYONS	Sapim, 28, straight pull, DBL Technology
PNEUS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GÉOMÉTRIE

CADRE	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longueur de tube de selle (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Angle de tube de selle	77,5°	77,8°	78,2°	77,5°	77,8°	78,2°	76,5°	76,9°	77,2°	76,5°	76,9°	
Longueur du tube supérieur (mm)	558	557	556	589	588	587	622	621	621	654	653	
Longueur du tube de direction (mm)	100			105			115			120		
Angle du tube de direction	62,7°	63,0°	63,4°	62,7°	63,0°	63,4°	62,7°	63,1°	63,4°	62,7°	63,1°	
Déport de fourche (mm)	44			44			44			44		
Chasse (mm)	147	144	141	147	144	141	147	144	141	147	144	
Empattement (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	
Longueur des bases (mm)	445	443	442	445	443	442	445	443	442	445	443	
Hauteur du boîtier de pédalier (mm)	29	24	19	29	24	19	29	24	19	29	24	19
Stack (mm)	633	630	627	638	635	632	647	644	641	652	649	
Reach (mm)	418	421	426	448	452	456	468	471	476	499	503	
Hauteur d'enjambement (mm)	714	718	723	733	738	742	746	750	755	762	766	
Largeur de cintre (mm)	800			800			800			800		
Longueur de potence (mm)	40			40			40			40		
Longueur des manivelles (mm)	165			170			170			170		
Diamètre des roues	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.