

REIGN ADVANCED 2



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Dried Matcha
RAHMEN	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
GABEL	Fox 38 Rhythm, 170mm, GRIP damper, 15x110 Kabolt X, 44mm offset
DÄMPFER	Fox Float Performance, 205/62.5, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Contact TR35, 800x35mm, 35mm rise
GRIFFE	Giant Tactal Pro Single
VORBAU	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SATTELSTÜTZE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SATTEL	Giant Romero SL
PEDALE	
ANTRIEB	
SCHALTHEBEL	Shimano SLX SL-M7100, 1x12
UMWERFER	N/A
SCHALTWERK	Shimano SLX RD-M7100
BREMSEN	Shimano BR-MT520, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
BREMSHEBEL	Shimano Deore BL-MT501
KASSETTE	Shimano Deore M6100, 10x51
KETTE	Shimano
KURBEL	Shimano SLX, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NABE	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, MicroSpline driver body
SPEICHEN	Sapim, 28, straight pull, DBL Technology
REIFEN	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRIEDATEN

RAHMEN	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sitzrohrlänge (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Sitzrohrwinkel	77.5°	77.8°	78.2°	77.5°	77.8°	78.2°	76.5°	76.9°	77.2°	76.5°	76.9°	77.2°
Oberrohrlänge (mm)	558	557	556	589	588	587	622	621	621	654	653	653
Steuerrohr-Länge (mm)	100			105			115			120		
Steuerrohr-Winkel	62.7°	63.0°	63.4°	62.7°	63.0°	63.4°	62.7°	63.1°	63.4°	62.7°	63.1°	63.4°
Gabelneigung (mm)	44			44			44			44		
Trail (mm)	147	144	141	147	144	141	147	144	141	147	144	141
Radstand (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Kettenstreben-Länge (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Tretlager-Höhe (mm)	29	24	19	29	24	19	29	24	19	29	24	19
Stack (mm)	633	630	627	638	635	632	647	644	641	652	649	646
Reach (mm)	418	421	426	448	452	456	468	471	476	499	503	507
Überstandshöhe (mm)	714	718	723	733	738	742	746	750	755	762	766	771
Lenkerbreite (mm)	800			800			800			800		
Vorbaulänge (mm)	40			40			40			40		
Kurbellänge (mm)	165			170			170			170		
Radgrösse	29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]			29" [F] 27.5" [R]		

Spezifikations-, Preis- und Farbänderungen vorbehalten.