



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Ergo 4
DISPLAY	Giant RideControl GO Lux
AKKU	Giant EnergyPak Smart 560Wh, integrated, 48V
CHARGER	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Moon Dust
RAHMEN	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
GABEL	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
DÄMPFER	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
KOMPONENTEN	
LENKER	Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°
GRIFFE	Giant Tactal Pro-E, tapered design, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Giant Contact Switch adjustable dropper, 30,9mm (S:110~140, M:140~170, L/XL: 170~200) MMX remote
SATTEL	Giant Romero, Neutral
ANTRIEB	
SCHALTHEBEL	Shimano Deore
SCHALTWERK	Shimano Deore, 12-speed shadow+
BREMSEN	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
BREMSHEBEL	Shimano SLX
KASSETTE	Shimano Deore, 10-51T, 12-speed
KETTE	Shimano Deore 12-speed
KURBEL	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

LAUFRÄDER	
FELGEN	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
NABE	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
SPEICHEN	Sapim Race [F] E-Lite [R], e-bike optimized
REIFEN	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRAS	Aegis Tire Checker
ACCESSORIES	
BELEUCHTUNG	Optional: - Giant Recon series e-bike lights available and direct connectable

GEOMETRIEDATEN

RAHMEN	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sitzrohlänge (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	235			260			285			310		
Sitzrohrwinkel	77.1° 77.5° 77.9°			77.1° 77.5° 77.9°			77.1° 77.5° 77.9°			77.1° 77.5°		
Oberrohrlänge (mm)	570 569 568			602 601 600			625 624 623			657 656 655		
Steuerrohr-Länge (mm)	95			105			120			135		
Steuerrohr-Winkel	63.1° 63.5° 63.9°			63.1° 63.5° 63.9°			63.1° 63.5° 63.9°			63.1° 63.5°		
Gabelneigung (mm)	44			44			44			44		
Trail (mm)	133.3 130.3 127.4			133.3 130.3 127.4			133.3 130.3 127.4			133.3 130.3		
Radstand (mm)	1226 1226 1227			1261 1261 1261			1287 1288 1288			1323 1323 1323		
Kettenstreben-Länge (mm)	450 450 450			450 450 450			450 450 450			450 450 450		
Tretlager-Höhe (mm)	10 5			10 5			10 5			10 5		
Stack (mm)	647 645 642			656 654 651			669 667 665			683 680 677		
Reach (mm)	426 430 435			456 460 465			476 480 485			505 510 515		
Lenkerbreite (mm)	800			800			800			800		
Vorbaulänge (mm)	40			40			40			40		
Kurbellänge (mm)	160			160			160			160		
Radgrösse	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" / F29"		

Spezifikations-, Preis- und Farbänderungen vorbehalten.