



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Lavender Blush, Carbon
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTEN	
LENKER	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIFFE	Stratus Lite 3.0
VORBAU	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATTELSTÜTZE	Giant D-Fuse, composite, 14mm offset
SATTEL	Giant Grit
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-610, 2x12
UMWERFER	Shimano GRX RX-820
SCHALTWERK	Shimano GRX RX-820
BREMSEN	Shimano BR-RX410hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano GRX RX-610 hydraulic
KASSETTE	Shimano CS-HG710, 12-speed, 11x36
KETTE	KMC X12L-1
KURBEL	Shimano FC-RX610-2, 30/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant P-X2 , alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Giant Crosscut Grip, 700x45c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Sitzrohlänge (mm)	430	450	470	490	510	530
Sitzrohrwinkel	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	540	550	560	575	585	600
Steuerrohr-Länge (mm)	125	135	150	165	180	195
Steuerrohr-Winkel	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68
Radstand (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051	1051 1061
Kettenstreben-Länge (mm)	425 435	425 435	425 435	425 435	425 435	425 435
Tretlager-Höhe (mm)	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	407
Überstandshöhe (mm)	724 731	740 747	757 764	774 780	791 797	807 814
Lenkerbreite (mm)	420	420	440	440	460	460
Vorbaulänge (mm)	50	60	70	80	80	90
Kurbellänge (mm)	170	170	172.5	172.5	175	175

Spezifikations-, Preis- und Farbänderungen vorbehalten.