



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Black/Rosso Corsa
CADRE	Advanced-grade Composite, 12x142mm thru-axle, disc
FOURCHE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
POIGNÉES	Stratus Lite 2.0
POTENCE	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
TIGE DE SELLE	Giant Variant, composite, -5/+15mm offset
SELLE	Giant Fleet SL
PÉDALES	platform pedal [GCS,GTS], N/A [all other GSC]
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano Dura-Ace Di2
DÉRAILLEUR AVANT	Shimano Dura-Ace Di2 FD-R9250
DÉRAILLEUR ARRIÈRE	Shimano Dura-Ace Di2 RD-R9250
FREINS	Shimano Dura-Ace Di2 hydraulic, Shimano RT-CL900 rotors [F]160mm, [R]140mm
LEVIER DE FREIN	Shimano Dura-Ace Di2
CASSETTE	Shimano Dura-Ace, 12-speed, 11x30
CHAÎNE	Shimano CN-M9100
PÉDALIER	Shimano Dura-Ace, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
PÉDALIER	Shimano, press fit

ROUES	
JANTES	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
MOYEUX	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
RAYONS	Giant Aero Carbon Spoke
PNEUS	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GÉOMÉTRIE

CADRE	XS	S	M	ML	L	XL
Longueur de tube de selle (mm)	425	445	470	500	530	560
Angle de tube de selle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longueur du tube supérieur (mm)	520	535	550	565	580	600
Longueur du tube de direction (mm)	120	130	145	165	185	200
Angle du tube de direction	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Déport de fourche (mm)	45	45	45	45	45	45
Chasse (mm)	72,1	64	59,2	59,2	59,2	59,2
Empattement (mm)	976	977	980	991	1006	1020
Longueur des bases (mm)	405	405	405	405	405	405
Hauteur du boîtier de pédalier (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Hauteur d'enjambement (mm)	719	734	752	768	786	803
Largeur de cintre (mm)	420	420	440	440	440	440
Longueur de potence (mm)	80	90	100	110	110	120
Longueur des manivelles (mm)	165	165	170	170	172,5	172,5

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.