



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Dark Chrome/Iris
RAHMEN	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
GABEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIFFE	Stratus Lite 2.0
VORBAU	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SATTELSTÜTZE	Giant Integrated Seatpost, -5/+15mm offset
SATTEL	Giant Fleet SLR
ANTRIEB	
SCHALTHEBEL	Shimano Ultegra Di2
UMWERFER	Shimano Ultegra Di2 FD-R8150
SCHALTWERK	Shimano Ultegra Di2 RD-R8150
BREMSEN	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
BREMSHEBEL	Shimano Ultegra Di2
KASSETTE	Shimano Ultegra, 12-speed, 11x34
KETTE	Shimano CN-M8100
KURBEL	Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
NABE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPEICHEN	Giant Aero Carbon Spoke
REIFEN	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	680	710	740	770	800	830
Sitzrohrwinkel	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Oberrohrlänge (mm)	520	535	550	565	580	600
Steuerrohr-Länge (mm)	120	130	145	165	185	200
Steuerrohr-Winkel	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Gabelneigung (mm)	45	45	45	45	45	45
Trail (mm)	72.1	64	59.2	59.2	59.2	59.2
Radstand (mm)	976	977	980	991	1006	1020
Kettenstreben-Länge (mm)	405	405	405	405	405	405
Tretlager-Höhe (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Überstandshöhe (mm)	719	734	752	768	786	803
Lenkerbreite (mm)	420	420	440	440	440	440
Vorbaulänge (mm)	80	90	100	110	110	120
Kurbellänge (mm)	165	165	170	170	172.5	172.5

Spezifikations-, Preis- und Farbänderungen vorbehalten.