

ANTHEM ADVANCED SL FRAME

GIANT



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Iris Drift
RAHMEN	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
DÄMPFER	RockShox SidLuxe Ultimate, RL damper, Solo Air, 210/50, TwistLoc Ultimate
KOMPONENTEN	
LENKER	Giant Integrated XC, composite, 780mm, 9-degree upsweep
VORBAU	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm

LAUFRÄDER	
EXTRAS	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIEDATEN

RAHMEN	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sitzrohrlänge (mm)	400		420		465		495	
Sitzrohrwinkel	75.5° 76.0°		75.5° 76.0°		75.5° 76.0°		75.5° 76.0°	
Oberrohrlänge (mm)	576 574		602 600		624 623		651 650	
Steuerrohr-Länge (mm)	90		95		105		115	
Steuerrohr-Winkel	66.5° 67.0°		66.5° 67.0°		66.5° 67.0°		66.5° 67.0°	
Gabelneigung (mm)	44		44		44		44	
Trail (mm)	116 112.2		115.9 112.2		115.9 112.2		115.8 112.2	
Radstand (mm)	1141 1140		1168 1167		1192 1191		1221 1220	
Kettenstreben-Länge (mm)	437 435		437 435		437 435		437 435	
Tretlager-Höhe (mm)	51 45		51 45		52 45		52 45	
Stack (mm)	602 599		607 603		616 612		626 622	
Reach (mm)	420 425		445 450		465 470		490 495	
Überstandshöhe (mm)	769 775		764 771		758 763		751 758	
Lenkerbreite (mm)	780		780		780		780	
Vorbaulänge (mm)	60		70		70		80	
Kurbellänge (mm)	170		170		175		175	

Spezifikations-, Preis- und Farbänderungen vorbehalten.