

ANTHEM ADVANCED SL SE



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Stormfire Sprint
RAHMEN	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GABEL	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
DÄMPFER	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
KOMPONENTEN	
LENKER	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIFFE	Giant XC Pro, silicone
VORBAU	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SATTELSTÜTZE	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm XL:150mm travel / 30.9 x 395mm
SATTEL	Giant Grit SLR
ANTRIEB	
SCHALTHEBEL	SRAM AXS Pod, 1x12
SCHALTWERK	SRAM XX SL Eagle Transmission
BREMSSEN	SRAM Motive ULT, custom color, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
BREMSEBEL	SRAM Motive ULT, custom color
KASSETTE	SRAM XS 1299 Eagle Transmission, 10x52
KETTE	SRAM XX SL Eagle Transmission
KURBEL	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	CADEX Max XC WheelSystem, 30mm inner width
NABE	[F] CADEX Max XC, CenterLock [R] CADEX Max XC, 132t ratchet driver, CenterLock
SPEICHEN	CADEX Max XC carbon
REIFEN	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, MRP 1x CS chain guide
LIMITS	
MAX TIRE CLEARANCE	2.4"
MAX CHAINRING SIZE	34T

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohrlänge (mm)	400	420	465	495
Sitzrohrwinkel	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Oberrohrlänge (mm)	576 574	602 600	624 623	651 650
Steuerrohr-Länge (mm)	90	95	105	115
Steuerrohr-Winkel	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	116 112.2	115.9 112.2	115.9 112.2	115.8 112.2
Radstand (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Kettenstreben-Länge (mm)	437 435	437 435	437 435	437 435
Tretlager-Höhe (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Überstandshöhe (mm)	769 775	764 771	758 763	751 758
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	60	70	70	80
Kurbellänge (mm)	170	170	175	175

Spezifikations-, Preis- und Farbänderungen vorbehalten.