

CONTEND AR 1



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, ML, L, XL
FARBE	Stardust Grey/Silver White
RAHMEN	ALUXX-SL Grade Aluminum 12x142mm thru-axle, Disc
GABEL	Advanced-Grade Composite, Full Carbon, OverDrive Steerer, 12x100mm thru-axle, Disc
KOMPONENTEN	
LENKER	Giant Contact (w/Flare) Reach 72mm & Drop 125mm
GRIFFE	Cork Tape w/ Gel VLT-001G
VORBAU	Giant Contact Aerolight
SATTELSTÜTZE	Giant D-Fuse Composite Offset 14mm
SATTEL	Giant Approach 7mm Steel Rail, with UniClip / ParticleFlow technology
ANTRIEB	
SCHALTHEBEL	Shimano CUES U6030
UMWERFER	Shimano Cues U6030
SCHALTWERK	Shimano Cues U6000
BREMSEN	Shimano BR-U6030 [F]160 [R]160
BREMSHEBEL	Shimano Cues U6030
KASSETTE	Shimano CS-LG400, 11x50, 11 speed
KETTE	KMC X11
KURBEL	Shimano CUES FC-U6030-1, 42
TRETLAGER	Shimano BB-RS501

LAUFRÄDER	
FELGEN	Giant P-AR, 12mm Thru-Axle
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Giant Gavia Fondo 2, 700X32C Tubeless

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	430	465	500	535	555	585
Sitzrohrwinkel	75.0°	74.0°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	515	535	550	565	580	595
Steuerrohr-Länge (mm)	115	135	150	170	190	215
Steuerrohr-Winkel	71.5°	71.8°	72.0°	72.5°	72.5°	72.5°
Gabelneigung (mm)	53	53	53	53	53	53
Trail (mm)	62.9	61.3	59.6	56.4	56.4	56.4
Radstand (mm)	994.4	1002.8	1010.6	1015.4	1030.6	1045.8
Kettenstreben-Länge (mm)	422	422	422	422	422	422
Tretlager-Höhe (mm)	80	80	80	80	80	80
Stack (mm)	539.2	559.1	574.3	595.3	614.4	638.2
Reach (mm)	370.5	374.7	379.9	383	392.2	399.9
Überstandshöhe (mm)	717.5	743.7	770.1	798.5	817	843.9
Lenkerbreite (mm)	400	400	420	420	440	440
Vorbaulänge (mm)	80	90	100	100	110	110
Kurbellänge (mm)	165	165	170	170	172.5	172.5
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.