

DEFY ADVANCED PRO 0



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Luminous Lagoon/Chrome
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, disc
GABEL	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTEN	
LENKER	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIFFE	Stratus Lite 3.0
VORBAU	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SATTELSTÜTZE	Giant D-Fuse SLR, composite, -5/+15mm offset
SATTEL	Giant Fleet SL
PEDALE	platform pedal [GCS,GTS] / N/A [all other GSC]
ANTRIEB	
SCHALTHEBEL	Shimano Ultegra Di2 ST-R8170
UMWERFER	Shimano Ultegra Di2 FD-R8150
SCHALTWERK	Shimano Ultegra Di2 RD-R8150
BREMSSEN	Shimano Ultegra hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano Ultegra Di2
KASSETTE	Shimano Ultegra, 12-speed, 11x34
KETTE	Shimano Ultegra
KURBEL	Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant SLR 0 40 Carbon Disc WheelSystem
NABE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle / [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	CADEX Classic, tubeless, 700x32c (33.5mm), folding
EXTRAS	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	410	445	480	515	535	565
Sitzrohrwinkel	74.5°	74.0°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	515	530	545	560	575	595
Steuerrohr-Länge (mm)	125	135	150	175	195	215
Steuerrohr-Winkel	70.5°	71.8°	72.5°	72.5°	72.5°	72.5°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	71.6	63.4	58.6	58.6	58.6	58.6
Radstand (mm)	995	994	998	1010	1025	1040
Kettenstreben-Länge (mm)	420	420	420	420	420	420
Tretlager-Höhe (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Überstandshöhe (mm)	705	733	762	796	814	841
Lenkerbreite (mm)	404	404	424	424	444	444
Vorbaulänge (mm)	80	90	100	100	110	110
Kurbellänge (mm)	165	165	170	170	172.5	172.5

Spezifikations-, Preis- und Farbänderungen vorbehalten.