

REIGN ADVANCED E+ 1



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro3X, 100Nm, 48V 800W max power, 400% max support ratio
STEUEREINHEIT	Giant RideControl Ergo 4
DISPLAY	Giant RideControl Go Lux
AKKU	Giant EnergyPak Smart 560X, 560Wh, 48V Giant EnergyPak Plus 280Wh range extender
CHARGER	Giant EnergyPak 4A Charger, 48V
RAHMEN	
RAHMEN	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
GABEL	Fox Float 38 Performance Elite, 180mm, GripX2 damper, 4-way adjust, 110x15, Kabolt X
DÄMPFER	Fox DHX Performance Elite, 205x65mm, LSC LSR Std Steel Spring custom tuned
KOMPONENTEN	
LENKER	Giant Contact SL TR35, 35mm rise, 5-degree upsweep, 9-degree backsweep, 35x800mm
GRIFFE	Giant Tactal Pro-E, tapered, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
VORBAU	Giant Contact SL 35, 40 mm
SATTELSTÜTZE	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SATTEL	Giant Romero, neutral
ANTRIEB	
SCHALTHEBEL	SRAM Eagle 90 Transmission
SCHALTWERK	SRAM 90 Eagle Transmission
BREMSEN	TRP EVO Expert, hydraulic disc, 4-piston, 220mm rotors [F/R]
BREMSEBEL	TRP EVO Expert
KASSETTE	SRAM Eagle Transmission, 10x52, 12-speed
KETTE	SRAM Eagle Transmission, Flattop, PowerLink, 12-speed
KURBEL	Praxis e-HD forged crankarm set, Q-factor: 168mm, length: 155mm

LAUFRÄDER	
FELGEN	Giant e-TRA 2, Hookless, 30mm inner width, Wide Guard
NABE	Giant E-Drive 260Nm, 72t engagement, Boost, 15x110mm[F] 12x148mm[R], e-bike optimized
SPEICHEN	Sapim Race [F] E-Lite [R], e-bike optimized
REIFEN	Maxxis Assagai 29x2.5" foldable, EXO+ 3C MaxxGrip [F] Maxxis Minion DHR II 27.5x2.4" WT foldable, DoubleDown, 3C MaxxGrip [R]
EXTRAS	Aegis Tire Checker, BLE+ tire pressure monitoring system Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
BELEUCHTUNG	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	156kg

GEOMETRIEDATEN

RAHMEN	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sitzrohrwinkel	77.1°	77.5°	77.9°	77.5°	77.9°	77.1°	77.5°	77.9°
Oberrohrlänge (mm)	570	569	568	601	600	625	624	623
Steuerrohr-Länge (mm)	95		105		120		135	
Steuerrohr-Winkel	63.1°	63.5°	63.9°	63.5°	63.9°	63.1°	63.5°	63.9°
Radstand (mm)	1226	1226	1227	1261	1261	1287	1288	1288
Kettenstreben-Länge (mm)	450	450	450	450	450	450	450	450
Stack (mm)	647	645	642	654	651	669	667	665
Reach (mm)	426	430	435	460	465	476	480	485
Kurbellänge (mm)	155		155		155		155	

Spezifikations-, Preis- und Farbänderungen vorbehalten.