

REVOLT ADVANCED SL 2

GIANT



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Deep Lagoon
RAHMEN	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
GABEL	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMPONENTEN	
LENKER	Giant Contact SLR XR Integrated XS:70x420mm, S:80x420mm, M:90x440mm, M/L:100x440mm, L:100x440mm, XL:110x460mm
GRIFFE	Stratus Lite 3.0
VORBAU	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
SATTELSTÜTZE	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SATTEL	Giant Grit SL
ANTRIEB	
SCHALTHEBEL	SRAM Rival AXS E1, 1x13
SCHALTWERK	SRAM Rival XPLR AXS E1
BREMSEN	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BREMSHEBEL	SRAM Rival E1 hydraulic
KASSETTE	SRAM Rival E1, 13-speed, 10x46
KETTE	SRAM Rival E1
KURBEL	SRAM Rival XPLR AXS with power meter, 42t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
NABE	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
SPEICHEN	Aero Bladed Carbon Spoke
REIFEN	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	53mm max tire size
MAX CHAINRING SIZE	54t max chainring size

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	430	450	470	490	510	530
Sitzrohrwinkel	75.0°	74.5°	74.5°	74.0°	74.0°	74.0°
Oberrohrlänge (mm)	530	540	550	565	580	590
Steuerrohr-Länge (mm)	90	100	120	135	155	180
Steuerrohr-Winkel	70.5°	71.0°	71.5°	72.0°	72.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	78	74	71	67	67	67
Radstand (mm)	1026	1027	1033	1039	1055	1066
Kettenstreben-Länge (mm)	433	433	433	433	433	433
Tretlager-Höhe (mm)	80	80	80	80	80	80
Stack (mm)	525	536	557	573	592	616
Reach (mm)	389	391	395	401	410	413
Überstandshöhe (mm)	726	743	762	779	798	818
Lenkerbreite (mm)	380	380	400	400	420	420
Vorbaulänge (mm)	70	80	90	100	100	110
Kurbellänge (mm)	165	165	170	170	172.5	172.5
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.