TRANCE ADVANCED E+ 1



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
STEUEREINHEIT	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
DISPLAY	RideControl GO Lux
AKKU	EnergyPak 840Wh, 48V
CHARGER	48V 4A Smart Charger X
RAHMEN	
GRÖSSEN	S/M/L/XL
RAHMEN	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
GABEL	Fox 36 Performance, 160mm travel, Grip damper
DÄMPFER	Fox Float X, Performance 2-position, 185x55mm Custom Tuned. Recommmended sag: 30%
KOMPONENTEN	
LENKER	Giant Contact SL Trail integrated, 27mm rise, Up: 5º Back: 8º, 800mm
GRIFFE	Giant Tactal Pro
VORBAU	Giant Contact SL Trail integrated, 40mm
SATTELSTÜTZE	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
SATTEL	Giant Romero SL HD
ANTRIEB	
SCHALTHEBEL	Sram AXS Pod Rocker, discrete clamp
SCHALTWERK	SRAM GX AXS
BREMSEN	TRP EVO Expert, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
BREMSHEBEL	TRP EVO Expert
KASSETTE	SRAM Eagle Transmission, XS-1270, 10-52T, 12-speed
KETTE	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
KURBEL	Praxis TYPE-2 alloy, SRAM Eagle Transmission 104BCD 36T

LAUFRÄDER	
FELGEN	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
NABE	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
SPEICHEN	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
REIFEN	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4"" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAS	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
SCHUTZBLECHE/KETTENSCHUTZ	Co-molded guide 32-36T adjustable

GEOMETRIEDATEN

RAHMEN	**S**	**M**	**L**	**XL**
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HI
Sitzrohrlänge (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	245	270	295	310
Sitzrohrwinkel	76.6° | 77.0° | 77.4°	76.6° | 77.0° | 77.4°	76.6° | 77.0° | 77.4°	76.6° | 77.0° | 7
Oberrohrlänge (mm)	568 | 567 | 566	605 | 604 | 603	630 | 629 | 628	662 | 661 | 660
Steuerrohr-Länge (mm)	110	120	130	140
Steuerrohr-Winkel	64.1° | 64.5° | 64.9°	64.1° | 64.5° | 64.9°	64.1° | 64.5° | 64.9°	64.1° | 64.5° | 6
Gabelneigung (mm)	44	44	44	44
Trail (mm)	135.9	135.9	135.9	135.9
Radstand (mm)	1200 | 1199 | 1197	1239 | 1237 | 1236	1267 | 1265 | 1264	1300 | 1299 | 12
Kettenstreben-Länge (mm)	443 | 443 | 443	443 | 443 | 443	443 | 443 | 443	443 | 443 | 443
Tretlager-Höhe (mm)	17 | 12 | 7	17 | 12 | 7	17 | 12 | 7	17 | 12 | 7
Stack (mm)	634 | 631 | 629	643 | 640 | 638	652 | 649 | 647	661 | 659 | 658
Reach (mm)	422 | 425 | 428	457 | 460 | 463	477 | 480 | 484	504 | 510 | 513
Lenkerbreite (mm)	800	800	800	800
Vorbaulänge (mm)	40	40	40	40
Kurbellänge (mm)	155	155	155	155
Radgrösse	29" [F], 27.5" [R]	29" [F], 27.5" [R]	29" [F], 27.5" [R]	29" [F], 27.5" [R]

Spezifikations-, Preis- und Farbänderungen vorbehalten.