



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
AKKU	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Ocean Twilight, Misty Lilac
RAHMEN	ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, integrated KSA40 kickstand mount
GABEL	SR Suntour NVX32 coil 29" 63mm travel 15x100 AH axle
DÄMPFER	n/a
KOMPONENTEN	
LENKER	Giant Contour GT, cable integrated, 30° back sweep, 31.8x660 mm
GRIFFE	Liv Comfort Ergo Microtech Plus
VORBAU	Aluminum angle adjustable stem
SATTELSTÜTZE	Suspension 2-bolt micro-adjustable, 30,9mm
SATTEL	Selle Royal Lift
PEDALE	Anti-slip Platform
ANTRIEB	
SCHALTHEBEL	Shimano Cues 9-speed
SCHALTWERK	Shimano Cues 9-speed
BREMSEN	Tektro HD-M281, hydraulic disc, 180mm [F] 160mm [R]
BREMSHEBEL	Tektro HD-M281
KASSETTE	Shimano Cues 11-36T, 9-speed
KETTE	KMC E9 Sport NP/BK, e-bike optimized
KURBEL	Aluminum 38T

LAUFRÄDER	
FELGEN	Liv GX03V 700c aluminium
NABE	Shimano center-lock 15x100mm [F], Shimano center-lock OLD 135mm [R]
SPEICHEN	Stainless steel
REIFEN	Maxxis MetroPass 28x2.2
ACCESSORIES	
BELEUCHTUNG	Recon E HL50 StZVO [F] Axa BlueLine Steady E6 [R]
SCHLOSS	ABUS Xplus battery lock
GEPÄCKTRÄGER	MIK System rack. Child seat, bag & basket compatible

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	380	430	460	495
Sitzrohrwinkel	74.0°	73.5°	73.0°	72.5°
Oberrohrlänge (mm)	565	580	600	620
Steuerrohr-Länge (mm)	180	180	200	200
Steuerrohr-Winkel	69.5°	69.5°	69.5°	69.5°
Gabelneigung (mm)	46	46	46	46
Trail (mm)	94.5	94.5	94.5	94.5
Radstand (mm)	1116	1137	1152	1165
Kettenstreben-Länge (mm)	482	482	482	482
Tretlager-Höhe (mm)	60	60	60	60
Stack (mm)	662	662	681	681
Reach (mm)	366	384	392	405
Überstandshöhe (mm)	427	428	431	437
Lenkerbreite (mm)	660	660	660	660
Vorbaulänge (mm)	60	80	80	100
Kurbellänge (mm)	165	165	170	170
Radgrösse	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.