



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Move Plus, Hub drive 75Nm max
SENSOR	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
AKKU	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Iron Rouge/ Carbon Smoke
RAHMEN	Advanced-grade composite,12x145 thru-axle
GABEL	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
DÄMPFER	-
KOMPONENTEN	
LENKER	Liv Contact SL D-Fuse 31.8 alloy
VORBAU	Contact SL Aerolight 31.8 alloy
SATTELSTÜTZE	Giant D-Fuse, Composite, 14mm offset
SATTEL	Liv Approach
ANTRIEB	
SCHALTHEBEL	Sram Rival AXS
UMWERFER	Sram Rival AXS
SCHALTWERK	Sram Rival AXS
BREMSSEN	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
BREMSHEBEL	Sram Rival AXS HRD
KASSETTE	Sram Rival XG-1250 10x36T 12-speed
KETTE	Sram Rival 12-speed
KURBEL	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS"
TRETLAGER	Giant E+ System BBSS

LAUFRÄDER	
FELGEN	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
REIFEN	Giant Gavia Fondo 0, tubeless, 700x32, folding
EXTRAS	Fender adapter
ACCESSORIES	
BELEUCHTUNG	Seatpost clamp integrated tail light

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	400	435	470	505
Sitzrohrwinkel	74.5°	74.5°	74.0°	73.5°
Oberrohrlänge (mm)	515	525	540	555
Steuerrohr-Länge (mm)	120	135	155	175
Steuerrohr-Winkel	70.5°	71.0°	72.0°	72.0°
Gabelneigung (mm)	50	50	50	50
Radstand (mm)	993	999	1003	1013
Kettenstreben-Länge (mm)	420	420	420	420
Tretlager-Höhe (mm)	80	80	80	75
Stack (mm)	529	545	563	582
Reach (mm)	368	374	378	382
Überstandshöhe (mm)	677	708	743	782
Lenkerbreite (mm)	380	400	400	420
Vorbaulänge (mm)	80	90	100	110
Radgrösse	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.