

AVAIL ADVANCED PRO 0



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XXS, XS, S, M, L
FARBE	Dreamy Blue/Carbon/Chrome
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, disc
GABEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Liv Contact SLR D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GRIFFE	Liv Stratus Elite 2.0
VORBAU	Giant Contact SL AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SATTELSTÜTZE	Giant D-Fuse SLR, composite, -5/+15mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SATTEL	Liv Alacra SL
ANTRIEB	
SCHALTHEBEL	Shimano Ultegra Di2 ST-R8170
UMWERFER	Shimano Ultegra Di2 FD-R8150
SCHALTWERK	Shimano Ultegra Di2 RD-R8150
BREMSEN	Shimano Ultegra hydraulic, Shimano RT-CL800 rotors, [F]160mm, [R]160mm
BREMSHEBEL	Shimano Ultegra hydraulic
KASSETTE	Shimano Ultegra, 12-speed, 11x34
KETTE	Shimano CN-M8100
KURBEL	Shimano Ultegra, 34/50 with Giant power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant SLR 0 40 WheelSystem, [F] 36mm, [R] 36mm
NABE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
SPEICHEN	Sapim CX-Ray
REIFEN	CADEX Classic 32, tubeless, 700x32c, folding
EXTRAS	two bottle cage, fender mount, computer mount, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRIEDATEN

RAHMEN	XXS	XS	S	M	L
Sitzrohlrlänge (mm)	385	405	435	465	495
Sitzrohrwinkel	75.0°	74.5°	74.5°	74.0°	74.0°
Oberrohrlänge (mm)	500	520	525	535	550
Steuerrohr-Länge (mm)	110	125	145	165	185
Steuerrohr-Winkel	69.8°	71.0°	71.0°	71.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50
Trail (mm)	76.2	68.3	68.3	68.3	61.8
Radstand (mm)	989	995	1002	1007	1013
Kettenstreben-Länge (mm)	420	420	420	420	420
Tretlager-Höhe (mm)	75	75	75	75	75
Stack (mm)	510	528	547	566	589
Reach (mm)	363	373	373	373	381
Überstandshöhe (mm)	683	712	737	762	789
Lenkerbreite (mm)	380	380	400	400	420
Vorbaulänge (mm)	70	70	80	90	90
Kurbellänge (mm)	160	165	165	170	172.5

Spezifikations-, Preis- und Farbänderungen vorbehalten.