



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XXS, XS, S, M, L
FARBE	Sandshell/Cold Night
RAHMEN	ALUXX-grade aluminum, 12x142mm thru-axle, disc
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Liv D-Fuse SL, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GRIFFE	Liv All Condition
VORBAU	Giant Contact, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SATTELSTÜTZE	Giant D-Fuse, composite, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SATTEL	Liv Approach
ANTRIEB	
SCHALTHEBEL	Shimano 105
UMWERFER	Shimano 105
SCHALTWERK	Shimano 105
BREMSEN	Shimano 105 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BREMSHEBEL	Shimano 105
KASSETTE	Shimano 105, 12-speed, 11x36
KETTE	KMC X12
KURBEL	Shimano 105, 34/50, XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
TRETLAGER	Shimano BB-R5501

LAUFRÄDER	
FELGEN	Giant P-R2 Disc, alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Giant Gavia Fondo 2, 700x32c, tubeless
EXTRAS	tubeless prepared, 38mm max tire size
LIMITS	
MAX TIRE CLEARANCE	38mm

GEOMETRIEDATEN

RAHMEN	XXS	XS	S	M	L
Sitzrohrlänge (mm)	395	430	465	500	535
Sitzrohrwinkel	75.0°	75.0°	74.5°	74.0°	74.0°
Oberrohrlänge (mm)	500	515	525	540	555
Steuerrohr-Länge (mm)	120	135	150	170	190
Steuerrohr-Winkel	70.0°	70.5°	72.0°	72.0°	72.0°
Gabelneigung (mm)	45	45	45	45	45
Trail (mm)	76.2	73	63.5	63.5	63.5
Radstand (mm)	986	998	990	1000	1016
Kettenstreben-Länge (mm)	420	420	420	420	420
Tretlager-Höhe (mm)	70	70	70	70	70
Stack (mm)	514	530	550	569	588
Reach (mm)	362	372	372	377	386
Überstandshöhe (mm)	662	687	716	744	772
Lenkerbreite (mm)	380	380	400	400	420
Vorbaulänge (mm)	70	70	80	90	90
Kurbellänge (mm)	160	165	165	170	172.5

Spezifikations-, Preis- und Farbänderungen vorbehalten.