



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, L
COLORIS	Camel Silk/Chrome
CADRE	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
FOURCHE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
COMPOSANTS	
CINTRE	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
POIGNÉES	Liv All Condition
POTENCE	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
TIGE DE SELLE	Giant D-Fuse, composite, -5/+15mm offset
SELLE	Liv Grit
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano GRX RX-820, 2x12
DÉRAILLEUR AVANT	Shimano GRX RX-820
DÉRAILLEUR ARRIÈRE	Shimano GRX RX-820
FREINS	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors, [F]160mm, [R]160mm
LEVIERS DE FREIN	Shimano GRX RX-820 hydraulic
CASSETTE	Shimano CS-HG710, 12-speed, 11x36
CHAÎNE	KMC X12L-1
PÉDALIER	Shimano GRX RX-820, 31/48, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
PÉDALIER	Shimano, press fit

ROUES	
JANTES	Giant CXR 2, [F] 35mm, [R] 35mm
MOYEUX	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
RAYONS	Sapim Sprint
PNEUS	CADEX GX, 700x40c, tubeless
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GÉOMÉTRIE

CADRE	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Longueur de tube de selle (mm)	390	420	465	500
Angle de tube de selle	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Longueur du tube supérieur (mm)	525 525	535 535	545 545	555 555
Longueur du tube de direction (mm)	90	110	140	160
Angle du tube de direction	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Déport de fourche (mm)	50	50	50	50
Chasse (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Empattement (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Longueur des bases (mm)	425 435	425 435	425 435	430 440
Hauteur du boîtier de pédalier (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Hauteur d'enjambement (mm)	681 688	708 715	748 755	779 786
Largeur de cintre (mm)	400	400	420	420
Longueur de potence (mm)	50	60	70	80
Longueur des manivelles (mm)	165	170	172,5	172,5

Giant Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.