



SPEZIFIKATIONEN

| RAHMEN       |                                                                                                                                 |
|--------------|---------------------------------------------------------------------------------------------------------------------------------|
| GRÖSSEN      | XS, S, M, L                                                                                                                     |
| FARBE        | Lunar Eclipse                                                                                                                   |
| RAHMEN       | Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage                |
| GABEL        | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings |
| DÄMPFER      | N/A                                                                                                                             |
| KOMPONENTEN  |                                                                                                                                 |
| LENKER       | Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm                       |
| GRIFFE       | Liv All Condition                                                                                                               |
| VORBAU       | Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm                                                        |
| SATTELSTÜTZE | Giant D-Fuse, composite, 14mm offset                                                                                            |
| SATTEL       | Liv Grit                                                                                                                        |
| ANTRIEB      |                                                                                                                                 |
| SCHALTHEBEL  | Shimano GRX RX-610, 2x12                                                                                                        |
| UMWERFER     | Shimano GRX RX-820                                                                                                              |
| SCHALTWERK   | Shimano GRX RX-820                                                                                                              |
| BREMSEN      | Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm                                                            |
| BREMSHEBEL   | Shimano GRX RX-610 hydraulic                                                                                                    |
| KASSETTE     | Shimano CS-HG710, 12-speed, 11x36                                                                                               |
| KETTE        | KMC X12L-1                                                                                                                      |
| KURBEL       | Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm                                                            |
| TRETLAGER    | Shimano, press fit                                                                                                              |

| LAUFRÄDER          |                                                                                                                                                       |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| FELGEN             | Giant P-X2 Disc, alloy                                                                                                                                |
| NABE               | Giant alloy, 12mm thru-axle                                                                                                                           |
| SPEICHEN           | Sapim                                                                                                                                                 |
| REIFEN             | Giant Crosscut Grip, 700x45c, tubeless                                                                                                                |
| EXTRAS             | 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag |
| LIMITS             |                                                                                                                                                       |
| MAX TIRE CLEARANCE | 53mm                                                                                                                                                  |

GEOMETRIEDATEN

| RAHMEN                   | XS            | S             | M             | L             |
|--------------------------|---------------|---------------|---------------|---------------|
|                          | SHORT   LONG  | SHORT   LONG  | SHORT   LONG  | SHORT   LONG  |
| Sitzrohlänge (mm)        | 390           | 420           | 465           | 500           |
| Sitzrohrwinkel           | 74.5°   74.4° | 74.5°   74.4° | 74.5°   74.4° | 74.5°   74.4° |
| Oberrohrlänge (mm)       | 525   525     | 535   535     | 545   545     | 555   555     |
| Steuerrohr-Länge (mm)    | 90            | 110           | 140           | 160           |
| Steuerrohr-Winkel        | 70.0°   69.9° | 70.5°   70.4° | 71.0°   70.9° | 71.0°   70.9° |
| Gabelneigung (mm)        | 50            | 50            | 50            | 50            |
| Trail (mm)               | 78.4   82     | 75   78.5     | 71.6   75.1   | 71.6   75     |
| Radstand (mm)            | 1012   1022   | 1019   1029   | 1026   1036   | 1043   1052   |
| Kettenstreben-Länge (mm) | 425   435     | 425   435     | 425   435     | 430   440     |
| Tretlager-Höhe (mm)      | 80   81       | 80   81       | 80   81       | 80   81       |
| Stack (mm)               | 523   524     | 544   545     | 574   575     | 593   594     |
| Reach (mm)               | 380   379     | 384   383     | 386   385     | 391   389     |
| Überstandshöhe (mm)      | 681   688     | 708   715     | 748   755     | 779   786     |
| Lenkerbreite (mm)        | 400           | 400           | 420           | 420           |
| Vorbaulänge (mm)         | 50            | 60            | 70            | 80            |
| Kurbellänge (mm)         | 165           | 170           | 172.5         | 172.5         |

Spezifikations-, Preis- und Farbänderungen vorbehalten.