

DEVOTE ADVANCED PRO



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, L
COLORIS	Nebula/Chrome
CADRE	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing
FOURCHE	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
POIGNÉES	Liv All Condition
POTENCE	Giant Contact AeroLight, -10 degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
TIGE DE SELLE	Giant D-Fuse SLR, composite, -5/+15mm offset
SELLE	Liv Grit SL
PÉDALES	platform pedal [GCS, GTS], no pedal [All other GSC]
DÉRAILLEUR	
MANETTES DÉRAILLEUR	SRAM Force AXS E1, 2x12
DÉRAILLEUR AVANT	SRAM Force AXS E1
DÉRAILLEUR ARRIÈRE	SRAM Force AXS D2
FREINS	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors, [F]160mm, [R]160mm
LEVIERS DE FREIN	SRAM Force AXS E1 hydraulic
CASSETTE	SRAM Force E1, 12-speed, 10x36
CHAÎNE	SRAM Force E1
PÉDALIER	SRAM Force D2 DUB, 30/43, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant CXR 1, [F] 35mm, [R] 35mm
MOYEURS	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
RAYONS	Sapim CX-Ray
PNEUS	CADEX GX, 700x40c, foldable, tubeless
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GÉOMÉTRIE

CADRE	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Longueur de tube de selle (mm)	390		420		465		500	
Angle de tube de selle	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°
Longueur du tube supérieur (mm)	525	525	535	535	545	545	555	555
Longueur du tube de direction (mm)	90		110		140		160	
Angle du tube de direction	70,0°	69,9°	70,5°	70,4°	71,0°	70,9°	71,0°	70,9°
Déport de fourche (mm)	50		50		50		50	
Chasse (mm)	78,4	82	75	78,5	71,6	75,1	71,6	75
Empattement (mm)	1012	1022	1019	1029	1026	1036	1043	1052
Longueur des bases (mm)	425	435	425	435	425	435	430	440
Hauteur du boîtier de pédalier (mm)	80	81	80	81	80	81	80	81
Stack (mm)	523	524	544	545	574	575	593	594
Reach (mm)	380	379	384	383	386	385	391	389
Hauteur d'enjambement (mm)	681	688	708	715	748	755	779	786
Largeur de cintre (mm)	400		400		420		420	
Longueur de potence (mm)	50		60		70		80	
Longueur des manivelles (mm)	165		170		172,5		172,5	

Giant Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.