

LANGMA ADVANCED 2 QOM



Spezifikationen

Rahmen	
Größen	XXS, XS, S, M, L
Farbe	Native Grey/Chrome
Rahmen	Advanced-grade Composite, 12x142mm thru-axle, disc
Gabel	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
Dämpfer	N/A
Komponenten	
Lenker	Liv Contact, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
Griffe	Liv Stratus Elite 2.0
Vorbau	Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
Sattelstütze	Giant Variant, composite, -5/+15mm offset
Sattel	Liv Approach
Pedale	platform pedal [GCS,GTS], N/A [all other GSC]
Antrieb	
Schalthebel	Shimano 105
Umwerfer	Shimano 105
Schaltwerk	Shimano 105
Bremsen	Shimano 105 hydraulic, Shimano SM-RT64 rotors, [F] 160mm, [R] 140mm
Bremshebel	Shimano 105 Di2
Kassette	Shimano 105, 12-speed, 11x36
Kette	KMC X12L-1
Kurbel	Shimano 105, 34/50 XXS: 165mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
Tretlager	Shimano, press fit

Laufräder	
Felgen	Giant P-R1, [F] 25mm, [R] 25mm
Nabe	12mm thru-axle
Speichen	stainless
Reifen	Giant Gavia Course 0, tubeless, 700x28c, folding
Extras	tubeless prepared, 33mm max tire size
Limits	
Max Tire Clearance	33mm

Geometriedaten

Rahmen	XXS	XS	S	M	L
Sitzrohlänge (mm)	390	420	450	480	510
Sitzrohrwinkel	75.0°	75.0°	74.5°	74.0°	73.5°
Oberrohrlänge (mm)	498	508	524	540	555
Steuerrohr-Länge (mm)	105	120	135	155	175
Steuerrohr-Winkel	70.0°	71.0°	72.0°	72.5°	72.5°
Gabelneigung (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Radstand (mm)	970	973	977	984	994
Kettenstreben-Länge (mm)	405	405	405	405	405
Tretlager-Höhe (mm)	72	72	70	70	70
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Überstandshöhe (mm)	685	707	736	763	783
Lenkerbreite (mm)	360	360	380	400	420
Vorbaulänge (mm)	80	80	90	100	110
Kurbellänge (mm)	160	165	165	170	172.5

Spezifikations-, Preis- und Farbänderungen vorbehalten.