

LANGMA ADVANCED PRO 0 QOM



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XXS, XS, S, M, L
COLORIS	Thundercloud
CADRE	Advanced-grade Composite, 12x142mm thru-axle, disc
FOURCHE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPOSANTS	
CINTRE	Liv Contact SLR , 31.8mm, 8-degree flare drop, XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
POIGNÉES	Liv Stratus Elite 2.0
POTENCE	Giant Contact SL AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
TIGE DE SELLE	Giant Variant, composite, -5/+15mm offset
SELLE	Liv Alacra SL
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano Ultegra Di2
DÉRAILLEUR AVANT	Shimano Ultegra Di2 FD-R8150
DÉRAILLEUR ARRIÈRE	Shimano Ultegra Di2 RD-R8150
FREINS	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors, [F]160mm, [R]140mm
LEVIER DE FREIN	Shimano Ultegra Di2
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CHAÎNE	Shimano CN-M8100
PÉDALIER	Shimano Ultegra, 34/50 with Giant Power Pro power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
PÉDALIER	Shimano, press fit

ROUES	
JANTES	Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm
MOYEUX	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
RAYONS	Giant Aero Carbon Spoke
PNEUS	CADEX Road Race GC, tubeless, 700x28c, folding
EXTRAS	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GÉOMÉTRIE

CADRE	XXS	XS	S	M	L
Longueur de tube de selle (mm)	390	420	450	480	510
Angle de tube de selle	75,0°	75,0°	74,5°	74,0°	73,5°
Longueur du tube supérieur (mm)	498	508	524	540	555
Longueur du tube de direction (mm)	105	120	135	155	175
Angle du tube de direction	70,0°	71,0°	72,0°	72,5°	72,5°
Déport de fourche (mm)	49	49	49	49	49
Chasse (mm)	74	68	61	58	58
Empattement (mm)	970	973	977	984	994
Longueur des bases (mm)	405	405	405	405	405
Hauteur du boîtier de pédalier (mm)	72	72	70	70	70
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Hauteur d'enjambement (mm)	685	707	736	763	783
Largeur de cintre (mm)	360	360	380	400	420
Longueur de potence (mm)	80	80	90	100	110
Longueur des manivelles (mm)	160	165	165	170	172,5

Giant Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.