

PIQUE ADVANCED SL SE



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, L
COLORIS	Stella Purple/Electric Rose
CADRE	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
FOURCHE	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
AMORTISSEUR	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
COMPOSANTS	
CINTRE	Giant Integrated XC, composite, 780mm, 9-degree upsweep
POIGNÉES	Liv XC Pro, silicone
POTENCE	Giant Integrated XC Carbon XS: 60, S:60mm, M:70mm, L:70mm
TIGE DE SELLE	RockShox Reverb AXS, pod controller remote XS: 100mm travel / 30.9 x 395mm S: 100mm travel / 30.9 x 395mm M: 100mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 3
SELLE	Liv Grit SL
PÉDALES	N/A
DÉRAILLEUR	
MANETTES DÉRAILLEUR	SRAM AXS Pod, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	SRAM XX SL Eagle Transmission
FREINS	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
LEVIER DE FREIN	SRAM Motive ULT
CASSETTE	SRAM XS 1299 Eagle Transmission, 10x52
CHAÎNE	SRAM XX SL Eagle Transmission
PÉDALIER	SRAM XX SL Eagle Transmission with Quark power meter, 32t, 55mm chainline XS: 165mm S:170mm, M:170mm, L:170mm
PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	XCR 29 carbon wheelsystem
MOYEURS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
RAYONS	Carbon
PNEUS	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP SL TR2 chain guide

GÉOMÉTRIE

CADRE	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Longueur de tube de selle (mm)	400	410	440	470
Angle de tube de selle	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Longueur du tube supérieur (mm)	555 554	572 571	594 593	611 610
Longueur du tube de direction (mm)	90	95	105	115
Angle du tube de direction	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Déport de fourche (mm)	44	44	44	44
Chasse (mm)	116 112	116 112	116 112	116 112
Empattement (mm)	1121 1120	1138 1138	1162 1162	1181 1180
Longueur des bases (mm)	437 435	437 435	437 435	437 435
Hauteur du boîtier de pédalier (mm)	51 45	51 45	51 45	51 45
Stack (mm)	602 599	607 603	616 612	625 622
Reach (mm)	399 405	415 421	435 440	450 455
Hauteur d'enjambement (mm)	772 778	770 776	765 765	759 765
Largeur de cintre (mm)	780	780	780	780
Longueur de potence (mm)	60	60	70	70
Longueur des manivelles (mm)	165	170	170	170

Giant Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.