



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	27.5": XS, S, 29": S, M, L
COLORIS	Black Diamond
CADRE	ALUXX-grade aluminum, disc
FOURCHE	Giant SXC32-3 RL Coil w/Pre-load Adj & 15x110 TA 1.5" Taper Steerer 27.5" XS: 80mm, S: 80mm 29" S: 100mm, M: 100mm, L: 100mm
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Connect Trail, 31.8mm 27.5" XS: 690mm, S: 690mm 29" S: 750mm, M: 750mm, L: 750mm
POIGNÉES	Giant Sole-O
POTENCE	Giant Sport, 7-degree 27.5" XS: 40mm, S: 40mm 29" S: 40mm, M: 50mm, L: 50
TIGE DE SELLE	Giant Contact Switch Core, 30.9mm 27.5" XS:100x350mm, S: 100x350mm 29" S: 100x350mm, M:100x400mm, L: 100x400mm
SELLE	Contact Ergo
PÉDALES	MTB caged
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano CUES SL-6000-10R, 1x10
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano CUES RD-U6000
FREINS	Tektro HDC TKD 149, hydraulic, Tektro rotors [F]180mm, [R]160mm
LEVIER DE FREIN	Tektro TKD 149, for small hands
CASSETTE	Shimano CUES CS-LG300, 11x48
CHAÎNE	KMC X11
PÉDALIER	ProWheel Charm, steel, 52.5mm chainline 32t (27.5") & 30t (29") 27.5" XS: 165mm, S: 165mm 29" S: 170mm, M: 170mm, L: 170mm
PÉDALIER	cartridge

ROUES	
JANTES	27.5": Giant GX03V 27.5", alloy, double wall, 21mm inner width 29": Giant GX03V 29", alloy, double wall, 21mm inner width
MOYEUX	alloy, sealed bearing
RAYONS	stainless, 14g
PNEUS	Maxxis Recon Race 27.5x2.4" or 29x2.4", 60tpi wire bead
EXTRAS	2.4" max tire size, max chainring 32T

GÉOMÉTRIE

CADRE	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")
Longueur de tube de selle (mm)	330	365	380	410	450
Seat Post Insertion Depth (mm)	280	310	330	360	220
Angle de tube de selle	74,0°	74,0°	74,5°	74,5°	74,0°
Longueur du tube supérieur (mm)	538	558	571	599	610
Longueur du tube de direction (mm)	90	95	90	100	105
Angle du tube de direction	67,0°	67,0°	67,5°	67,5°	68,5°
Déport de fourche (mm)	44	44	44	44	51
Chasse (mm)	105,2	105,2	108,9	108,9	94,3
Empattement (mm)	1080	1101	1129	1158	1160
Longueur des bases (mm)	440	440	455	455	455
Hauteur du boîtier de pédalier (mm)	45	45	55	55	55
Stack (mm)	548	553	593	602	610
Reach (mm)	381	400	407	432	435
Hauteur d'enjambement (mm)	680	689	689	708	757
Largeur de cintre (mm)	690	690	750	750	750
Longueur de potence (mm)	40	40	40	50	50
Longueur des manivelles (mm)	165	165	170	170	175
Diamètre des roues	27.5"	27.5"	29"	29"	29"

Giant Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.