

DEVOTE ADVANCED SL 2



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Misty Aloe
RAHMEN	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
GABEL	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMponenten	
LENKER	Liv Contact SLR XR Integrated XS: 70x380/420mm, S: 70x380/420mm, M: 80x380/420mm, L: 90x400/440mm
GRIFFE	Liv Stratus Elite 3.0
VORBAU	Liv Contact SLR XR Integrated XS: 70mm, S: 70mm, M: 80mm, L: 90mm
SATTELSTÜTZE	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SATTEL	Liv Grit SL
ANTRIEB	
SCHALTHEBEL	SRAM Rival AXS E1, 1x13
SCHALTWERK	SRAM Rival XPLR AXS E1
BREMSEN	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
BREMSHEBEL	SRAM Rival E1 hydraulic
KASSETTE	SRAM Rival E1, 13-speed, 10x46
KETTE	SRAM Rival E1
KURBEL	SRAM Rival XPLR AXS with power meter, 40t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
NABE	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
SPEICHEN	Aero Bladed Carbon Spoke
REIFEN	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	53mm max tire size
MAX CHAINRING SIZE	54t max chainring size

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	390	420	465	500
Sitzrohrwinkel	75.0°	74.5°	74.5°	74.0°
Oberrohrlänge (mm)	528	538	548	562
Steuerrohr-Länge (mm)	90	100	120	130
Steuerrohr-Winkel	70.5°	71.0°	71.5°	72.0°
Gabelneigung (mm)	50	50	50	50
Trail (mm)	75	72	69	65
Radstand (mm)	1024	1025	1031	1036
Kettenstreben-Länge (mm)	433	433	433	433
Tretlager-Höhe (mm)	80	80	80	80
Stack (mm)	525	537	557	569
Reach (mm)	387	389	394	399
Überstandshöhe (mm)	663	714	752	801
Lenkerbreite (mm)	380	380	380	400
Vorbau-Länge (mm)	70	70	80	90
Kurbellänge (mm)	165	165	170	172.5
Radgrösse	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.