



INTRIGUE ADVANCED E+ 1



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 4, 120 Nm, 48 V, 850 W peak power
STEUEREINHEIT	Giant RideControl Ergo 5 wireless, Integrated E+ System & seatpost remote
CLASSIFICATION	ASTM/EN Class 4 EN17406 / ISO4210-2M
DISPLAY	Giant RideControl Go Lux
AKKU	Giant EnergyPak Smart 560X, 560 Wh, 48 V and Giant EnergyPak Plus 280 Wh range extender
CHARGER	Giant Smart Charger X, 48 V 4A
RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Stardust Grey
RAHMEN	Advanced-grade composite frame, Advanced Forged Composite upper rocker, 150mm Maestro suspension system, 3-position flip chip adjustable geometry, 148 mm BOOST hub spacing, Z566/Z566 headset compatible
GABEL	FOX 36 Performance, 160mm travel, GRIP damper
DÄMPFER	FOX Float X, Performance 2-position, 185 x 55 mm, custom tuned, recommended sag 30%
KOMPONENTEN	
LENKER	Giant Contact SL Trail integrated, 27 mm rise, Up: 5° Back: 8°, XS & S: 760 mm, M & L: 780 mm
GRIFFE	Liv Tactal Pro
VORBAU	Giant Contact SL Trail Integrated, 40 mm
SATTELSTÜTZE	Giant Contact Switch E+, 30.9 mm, electronic dropper post
SATTEL	Liv Sylvia SL HD
ANTRIEB	
SCHALTHEBEL	SRAM AXS Pod Rocker, discrete clamp
SCHALTWERK	SRAM GX AXS Transmission
BREMSEN	TRP EVO Expert, hydraulic disc, 4-piston, 220 mm [F] 200 mm [R]
BREMSEBEL	TRP EVO Expert
KASSETTE	SRAM Eagle Transmission, XS-1270, 10-52T, 12-speed
KETTE	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
KURBEL	Praxis Type-2 alloy, 155 mm, SRAM Eagle Transmission, 104 BCD, 36T

LAUFRÄDER	
FELGEN	Giant TRA HD, Alloy, 30 mm inner width, Wide Guard Technology
NABE	Giant TRA HD, E-Drive, titanium ratchet system, 72T engagement, 15 x 110 mm [F] 12 x 148 mm [R], e-bike optimized
SPEICHEN	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
REIFEN	Maxxis Assegai 29 X 2.50-inch foldable, TLR, EXO+, 3C MaxxGrip [F] Maxxis Minion DHR II 27.5 x 2.4-inch foldable, TLR, EXO+, MaxxTerra [R]
EXTRAS	Giant Aegis Tire Checker, tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
BELEUCHTUNG	Optional: Giant Recon series e-bike lights available and direct-connect compatible
SCHUTZBLECHE/KETTENSCHUTZ	Co-molded guide 32-36T adjustable
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	140 kg

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Sitzrohrlänge (mm)	380	400	425	450
Seat Post Insertion Depth (mm)	225	245	270	290
Sitzrohrwinkel	76.6° 77.0° 77.4°	76.6° 77.0° 77.4°	76.6° 77.0° 77.4°	76.6° 77.0° 77.4°
Oberrohrlänge (mm)	552 550 548	565 563 561	598 596 594	625 623 621
Steuerrohr-Länge (mm)	95	105	115	125
Steuerrohr-Winkel	64.1° 64.5° 64.9°	64.1° 64.5° 64.9°	64.1° 64.5° 64.9°	64.1° 64.5° 64.9°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	125.4 122.5 119.6	125.4 122.5 119.6	125.4 122.5 119.6	125.4 122.5 119.6
Radstand (mm)	1184 1183 1182	1199 1198 1197	1232 1231 1230	1264 1260 1257
Kettenstreben-Länge (mm)	443	443	443	443
Tretlager-Höhe (mm)	17 12 7	17 12 7	17 12 7	17 12 7
Stack (mm)	620 618 615	629 627 624	638 636 633	647 645 642
Reach (mm)	409 412 415	420 423 426	448 452 455	476 477 478
Überstandshöhe (mm)	722 727 732	730 735 740	730 735 740	727 732 737
Lenkerbreite (mm)	760	760	780	780
Vorbaulänge (mm)	40	40	40	40
Kurbellänge (mm)	155	155	155	155
Radgrösse	29" [F], 27.5" [R]	29" [F], 27.5" [R]	29" [F], 27.5" [R]	29" [F], 27.5" [R]

Spezifikations-, Preis- und Farbänderungen vorbehalten.