



INTRIGUE ADVANCED E+ 2



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 4, 120 Nm, 48 V, 850 W peak power
STEUEREINHEIT	Giant RideControl Ergo 4
CLASSIFICATION	ASTM/EN Class 4 EN17406 / ISO4210-2M
DISPLAY	Giant RideControl Go Lux
AKKU	Giant EnergyPak Smart 560X, 560 Wh, 48 V
CHARGER	Giant Smart Charger X, 48 V 4A
RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Ember Violet
RAHMEN	Advanced-grade composite frame, Advanced Forged Composite upper rocker, 150mm Maestro suspension system, 3-position flip chip adjustable geometry, 148 mm BOOST hub spacing, ZS66/ZS66 headset compatible
GABEL	RockShox Psylo Gold RC, 160mm travel, Isolator RC damper, 15 x 110 mm BOOST Maxle Stealth axle
DÄMPFER	RockShox Deluxe Select, 185 x 55 mm, custom tuned, recommended sag 30%
KOMPONENTEN	
LENKER	Giant Contact TR35, 35 mm rise, Up: 5° Back: 9°, XS & S: 760 mm, M & L: 780 mm
GRIFFE	Liv Tactal Pro
VORBAU	Giant Contact SL 35, 40 mm
SATTELSTÜTZE	Giant Contact Switch AT, 30.9 mm travel-adjust dropper post, XS & S: 110-140 mm, M & L: 140-170 mm
SATTEL	Liv Sylvia HD
ANTRIEB	
SCHALTHEBEL	Shimano Deore, SL-6200, 12-speed
SCHALTWERK	Shimano Deore, RD-7200, 12-speed Shadow+
BREMSEN	TRP EVO Comp, hydraulic disc, 4-piston, 220 mm [F] 203 mm [R]
BREMSEBEL	TRP EVO Comp
KASSETTE	Shimano Deore, HyperGlide+, 12-speed, 11-51T
KETTE	KMC e12HT, high-torque e-bike optimized chain 12-speed
KURBEL	Praxis Type-2 alloy, 155 mm, Praxis 36T

LAUFRÄDER	
FELGEN	Giant TRA HD, alloy, 30 mm inner width, Wide Guard Technology
NABE	Giant TRA HD, E-Drive, titanium ratchet system, 72T engagement, 15 x 110 mm [F] 12 x 148 mm [R], e-bike optimized
SPEICHEN	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
REIFEN	Maxxis Assegai 29 X 2.50-inch Foldable, TLR, EXO+, 3C MaxxGrip [F] Maxxis Minion DHR II 27.5 x 2.4-inch Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAS	Giant Aegis Tire Checker, tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
BELEUCHTUNG	Optional: Giant Recon series e-bike lights available and direct-connect compatible
SCHUTZBLECHE/KETTENSCHUTZ	Co-molded guide 32-36T adjustable
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	156 kg

GEOMETRIEDATEN

RAHMEN	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sitzrohrlänge (mm)	380			400			425			450		
Seat Post Insertion Depth (mm)	225			245			270			290		
Sitzrohrwinkel	76.6° 77.0° 77.4°			76.6° 77.0° 77.4°			76.6° 77.0° 77.4°			76.6° 77.0°		
Oberrohrlänge (mm)	552 550 548			565 563 561			598 596 594			625 623 621		
Steuerrohr-Länge (mm)	95			105			115			125		
Steuerrohr-Winkel	64.1° 64.5° 64.9°			64.1° 64.5° 64.9°			64.1° 64.5° 64.9°			64.1° 64.5°		
Gabelneigung (mm)	44			44			44			44		
Trail (mm)	125.4 122.5 119.6			125.4 122.5 119.6			125.4 122.5 119.6			125.4 122.5		
Radstand (mm)	1184 1183 1182			1199 1198 1197			1232 1231 1230			1264 1260 1256		
Kettenstreben-Länge (mm)	443			443			443			443		
Tretlager-Höhe (mm)	17 12 7			17 12 7			17 12 7			17 12 7		
Stack (mm)	620 618 615			629 627 624			638 636 633			647 645 643		
Reach (mm)	409 412 415			420 423 426			448 452 455			476 477 478		
Überstandshöhe (mm)	722 727 732			730 735 740			730 735 740			727 732 737		
Lenkerbreite (mm)	760			760			780			780		
Vorbaulänge (mm)	40			40			40			40		
Kurbellänge (mm)	155			155			155			155		
Radgrösse	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

Spezifikations-, Preis- und Farbänderungen vorbehalten.