

INTRIGUE X ADVANCED 1



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Supernova Grey/Chrome
RAHMEN	Advanced-grade composite front and rear triangles, 140mm Maestro Suspension, 12x148mm thru-axle, flip chip – Maestro 3, flip chip – headset, integrated down tube storage, under-top tube storage mounts
GABEL	Fox 36 Float Factory, 150mm, GRIP X damper, Boost 15x110 Kabolt X, tapered, 44mm offset
DÄMPFER	Fox Float X Factory, two-position LSC adjust, 185x52.5, custom tuned for Liv, recommended sag 30%
KOMPONENTEN	
LENKER	Giant Contact SLR TR35, 20mm rise, composite XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIFFE	Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm
VORBAU	Giant Contact SL 35 XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SATTELSTÜTZE	Giant Contact Switch AT dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm
SATTEL	Liv Sylvia
PEDALE	platform [GC, GT]
ANTRIEB	
SCHALTHEBEL	SRAM AXS Pod, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM GX Eagle, T-Type AXS
BREMSEN	TRP EVO Pro, hydraulic, TRP rotors [F] 203mm, [R] 180mm
BREMSEBEL	TRP EVO Pro
KASSETTE	SRAM GX CS 1275 T-Type, 10x52
KETTE	SRAM GX T-Type
KURBEL	SRAM GX T-Type, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant TRX WheelSystem, carbon, hookless, 30mm rim inner width, 40mm outer width, 22mm height, Wide Guard Technology XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
NABE	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, XD driver body
SPEICHEN	Sapim, 28, straight pull, DBL Technology
REIFEN	Size XS, S, M and L, [F]: Maxxis Assegai 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Minion DHR II 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Minion DHR II 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 34t

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Sitzrohrlänge (mm)	370	390	420	450
Seat Post Insertion Depth (mm)	240	260	290	320
Sitzrohrwinkel	76.2° 76.6° 76.9°	76.2° 76.6° 76.9°	76.8° 77.2° 77.5°	76.8° 77.2°
Oberrohrlänge (mm)	548 547 546	564 563 562	582 581 580	603 602 601
Steuerrohr-Länge (mm)	95	100	105	110
Steuerrohr-Winkel	64.4° 64.8° 65.1°	64.4° 64.8° 65.1°	64.4° 64.8° 65.1°	64.4° 64.8°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	134.2 131.3 128.3	134.1 131.3 128.3	134.1 131.3 128.3	134 131.3 128.3
Radstand (mm)	1159 1159 1158	1176 1176 1175	1202 1201 1201	1224 1224 1223
Kettenstreben-Länge (mm)	440 439 438	440 439 438	440 439 438	440 439 438
Tretlager-Höhe (mm)	25 20 15	25 20 15	40 35 30	40 35 30
Stack (mm)	615 613 610	620 617 614	621 619 616	626 623 620
Reach (mm)	397 401 405	412 415 420	436 440 444	456 459 463
Überstandshöhe (mm)	730 734 738	733 737 742	745 749 754	767 771 775
Lenkerbreite (mm)	760	760	760	780
Vorbaulänge (mm)	40	50	50	50
Kurbellänge (mm)	165	170	170	170

Spezifikations-, Preis- und Farbänderungen vorbehalten.