

LANGMA ADVANCED PRO 0 - QOM



SPEZIFIKATIONEN

RAHMEN	
RAHMEN	Advanced-Grade Composite, 12x142mm thru-axle, Disc
GABEL	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
KOMPONENTEN	
LENKER	Liv Contact SLR
GRIFFE	Liv Stratus Elite 2.0
VORBAU	Giant Contact SL Aerolight, -10 degree
SATTELSTÜTZE	Giant Variant, Composite
SATTEL	Liv Alacra SL
PEDALE	GCS,GTS:Platform Pedal Rest GSC : no pedal
ANTRIEB	
SCHALTHEBEL	Shimano Ultegra Di2 HRD
UMWERFER	Shimano Ultegra Di2
SCHALTWERK	Shimano Ultegra Di2
BREMSSEN	Shimano Ultegra Di2 HRD
BREMSEBEL	Shimano Ultegra Di2 HRD
KASSETTE	Shimano Ultegra, 11x34
KETTE	Shimano CN-M8100, 12-speed
KURBEL	Shimano Ultegra, 34/50 w/ Powerpro
TRETLAGER	Shimano, PressFit 71

LAUFRÄDER	
FELGEN	Giant SLR 0 40 Carbon Disc Wheel System with Giant patented DBL (Dynamic Balanced Lacing) technology
NABE	Giant SLR 0 40 Carbon Disc Wheel System with Giant patented DBL (Dynamic Balanced Lacing) technology
SPEICHEN	Giant SLR 0 40 Carbon Disc Wheel System with Giant patented DBL (Dynamic Balanced Lacing) technology
REIFEN	CADEX Road Race GC Tubeless 700x30mm 240 TPI, Folding
EXTRAS	Computer mount, tubeless prepared
LIMITS	
MAX TIRE CLEARANCE	700x33mm

GEOMETRIEDATEN

RAHMEN	XXS	XS	S	M	L
Sitzrohrwinkel	75.0°	75.0°	74.5°	74.0°	73.5°
Oberrohrlänge (mm)	498	508	524	540	555
Steuerrohr-Länge (mm)	105	120	135	155	175
Steuerrohr-Winkel	70.0°	71.0°	72.0°	72.5°	72.5°
Radstand (mm)	970	973	977	984	994
Kettenstreben-Länge (mm)	405	405	405	405	405
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Überstandshöhe (mm)	685	707	736	763	783
Kurbellänge (mm)	160	165	165	170	172.5

Spezifikations-, Preis- und Farbänderungen vorbehalten.