LANGMA ADVANCED-UI2



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XXS, XS, S, M, L
RAHMEN	Advanced-grade Composite, 12x142mm thru-axle, disc
GABEL	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
KOMPONENTEN	
LENKER	Liv Contact, 31.8mm, Reach 68mm & Drop 120mm (360-380mm), Reach 72mm & Drop 125mm (400-410mm) XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIFFE	Liv Stratus Elite 2.0
VORBAU	Giant Contact Aerolight, -10° XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SATTELSTÜTZE	Giant Variant, composite
SATTEL	Liv Approach
ANTRIEB	
SCHALTHEBEL	Shimano Ultegra Di2 HRD
UMWERFER	Shimano Ultegra Di2
SCHALTWERK	Shimano Ultegra Di2
BREMSEN	Shimano Ultegra Di2 HRD hydraulic, Shimano RT-CL700 rotors [F] 160mm, [R] 140mm
BREMSHEBEL	Shimano Ultegra Di2 HRD
KASSETTE	Shimano CS-R8100, 11x34
KETTE	Shimano CN-M8100, 12-speed
KURBEL	Shimano Ultegra, 30/51 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
TRETLAGER	Shimano, press fit 71

LAUFRÄDER	
FELGEN	Giant SLR 2 40 Carbon Disc WheelSystem, with Giant patented DBL (Dynamic Balanced Lacing) technology
NABE	Giant SLR 2 40 WheelSystem hubs (integrated)
REIFEN	Giant Gavia Course 0 tubeless, 700x30c, 170 TPI, folding
LIMITS	
MAX TIRE CLEARANCE	700x33mm

GEOMETRIEDATEN

RAHMEN	XXS	XS	S	M	L
Sitzrohrlänge (mm)	390	420	450	480	510
Sitzrohrwinkel	75.0°	75.0°	74.5°	74.0°	73.5°
Oberrohrlänge (mm)	498	508	524	540	555
Steuerrohr-Länge (mm)	105	120	135	155	175
Steuerrohr-Winkel	70.0°	71.0°	72.0°	72.5°	72.5°
Gabelneigung (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Radstand (mm)	970	973	977	984	994
Kettenstreben-Länge (mm)	405	405	405	405	405
Tretlager-Höhe (mm)	72	72	70	70	70
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Überstandshöhe (mm)	685	707	736	763	783
Lenkerbreite (mm)	360	360	380	400	420
Vorbaulänge (mm)	80	80	90	100	110
Kurbellänge (mm)	160	165	165	170	172.5

Spezifikations-, Preis- und Farbänderungen vorbehalten.