



PIQUE ADVANCED SL SE



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Stella Storm
RAHMEN	Advanced SL-grade composite front and rear triangles, 120 mm FlexPoint Pro suspension, flip chip, 12x148 mm thru-axle
GABEL	RockShox SID Ultimate Flight Attendant, 120 mm, Flight Attendant Race Day damper, 15 x 110 mm BOOST, 44mm offset, custom decals
DÄMPFER	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210 x 50 mm, custom decals
KOMPONENTEN	
LENKER	Giant Contact SLR XC Integrated, composite, 780 mm, 9° backsweep, 2° upsweep
GRIFFE	Liv XC Pro, silicone
VORBAU	"Giant Contact SLR XC Integrated, composite XS: 60 mm, S: 60 mm, M: 70 mm, L: 70 mm"
SATTELSTÜTZE	"RockShox Reverb AXS, pod controller remote XS: 100 mm travel / 30.9 x 395 mm S: 100 mm travel / 30.9 x 395 mm M: 100 mm travel / 30.9 x 395 mm L: 125 mm travel / 30.9 x 395 mm"
SATTEL	Liv Grit SLR
ANTRIEB	
SCHALTHEBEL	SRAM AXS Pod Rocker Controller, MMX, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM XX SL Eagle Transmission
BREMSSEN	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors, [F] 180 mm, [R] 160 mm, custom caliper graphics
BREMSHEBEL	SRAM Motive ULT, custom graphics
KASSETTE	SRAM XS-1299 Eagle Transmission, 10-52T
KETTE	SRAM XX SL Eagle Transmission
KURBEL	"SRAM XX SL Eagle Transmission with Quarq power meter, 32T, 55 mm chainline XS: 165 mm S: 170 mm, M: 170 mm, L: 170 mm"
TRETLAGER	SRAM DUB, press-fit

LAUFRÄDER	
FELGEN	CADEX Max XC WheelSystem, 30 mm inner width
NABE	"[F] CADEX Max XC, CenterLock, one-piece integrated hub and spokes [R] CADEX Max XC M1-C120, 120T Helical-Bevel Ratchet Driver, CADEX Wave Spring, CenterLock, one-piece integrated hub and spokes"
SPEICHEN	CADEX Super Aero carbon with lightweight titanium thread
REIFEN	Maxxis Aspen [F/R], 29 x 2.4 in, foldable, 120 TPI, MaxxSpeed, EXO, tubeless
EXTRAS	Tubeless prepared, 2.4 in max tire size, 34T max chainring size, MRP SL TR2 chain guide, top-cap computer mount

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohrlänge (mm)	400	410	440	470
Sitzrohrwinkel	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°	75.5° 76.0°
Oberrohrlänge (mm)	555 554	572 571	594 593	611 610
Steuerrohr-Länge (mm)	90	95	105	115
Steuerrohr-Winkel	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°	66.5° 67.0°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	116 112	116 112	116 112	116 112
Radstand (mm)	1121 1120	1138 1138	1162 1162	1181 1180
Kettenstreben-Länge (mm)	437 435	437 435	437 435	437 435
Tretlager-Höhe (mm)	51 45	51 45	51 45	51 45
Stack (mm)	602 599	607 603	616 612	625 622
Reach (mm)	399 405	415 421	435 440	450 455
Überstandshöhe (mm)	772 778	770 776	765 765	759 765
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	60	60	70	70
Kurbellänge (mm)	165	170	170	170

Spezifikations-, Preis- und Farbänderungen vorbehalten.