



CARACTÉRISTIQUES TECHNIQUES

TECHNOLOGIE HYBRID	
MOTOR	Giant SyncDrive Pro 3, 90Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Ergo 4
DISPLAY	Giant RideControl GO Lux
BATTERIE	Giant EnergyPak Smart 560Wh, integrated, 48V
CHARGER	Giant EnergyPak smart charger 4A, 48V
CONNECTIVITY	Aegis Tire Checker included in RideControl display
CADRE	
TAILLES	S, M, L, XL
COLORIS	Moon Dust
CADRE	Advanced-grade composite frame, Advanced forged composite upper rocker, 170mm Maestro suspension system
FOURCHE	RockShox Zeb select, 29", 180mm travel, Charge RC damper, 44mm offset, Maxle Stealth, 110x15mm Boost axle
AMORTISSEUR	Fox Float X Performance, EVOL Large Volume sleeve, 205x65mm Trunnion mount, custom tuned
COMPOSANTS	
CINTRE	Giant Contact SL TR35, 35x800mm, 35mm rise, Up: 5° Back: 9°
POIGNÉES	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Giant Contact Switch adjustable dropper, 30,9mm (S:110-140, M:140-170, L/XL: 170-200) MMX remote
SELLE	Giant Romero, Neutral
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano Deore
DÉRAILLEUR ARRIÈRE	Shimano Deore, 12-speed shadow+
FREINS	Shimano SLX, hydraulic disc, 4-piston, 220mm [F/R]
LEVIERS DE FREIN	Shimano SLX
CASSETTE	Shimano Deore, 10-51T, 12-speed
CHAÎNE	Shimano Deore 12-speed
PÉDALIER	Praxis 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (Q-Factor:168mm, Length: 160mm)

ROUES	
JANTES	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] 27.5" [R]
MOYEUX	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm[F] 12x148mm[R], e-bike optimized
RAYONS	Sapim Race [F] E-Lite [R], e-bike optimized
PNEUS	Maxxis Assagai 29x2.5" foldable, tubeless, EXO+ 3C MaxxGrip[F] Maxxis MINION DHR II 27.5x2.4" WT foldable, Tubeless, DoubleDown, 3C MaxxGrip Compound [R]
EXTRAS	Aegis Tire Checker
ACCESSOIRES	
ÉCLAIRAGE	Optional: - Giant Recon series e-bike lights available and direct connectable

GÉOMÉTRIE

CADRE	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Longueur de tube de selle (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	235			260			285			310
Angle de tube de selle	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°	77,5°	77,9°	77,1°
Longueur du tube supérieur (mm)	570	569	568	602	601	600	625	624	623	657
Longueur du tube de direction (mm)	95			105			120			135
Angle du tube de direction	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°	63,5°	63,9°	63,1°
Déport de fourche (mm)	44			44			44			44
Chasse (mm)	133,3	130,3	127,4	133,3	130,3	127,4	133,3	130,3	127,4	133,3
Empattement (mm)	1226	1226	1227	1261	1261	1261	1287	1288	1288	1323
Longueur des bases (mm)	450	450	450	450	450	450	450	450	450	450
Hauteur du boîtier de pédalier (mm)	10	5		10	5		10	5		10
Stack (mm)	647	645	642	656	654	651	669	667	665	683
Reach (mm)	426	430	435	456	460	465	476	480	485	505
Largeur de cintre (mm)	800			800			800			800
Longueur de potence (mm)	40			40			40			40
Longueur des manivelles (mm)	160			160			160			160
Diamètre des roues	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"			R27.5" / F29"

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.