

REVOLT ADVANCED PRO 0

GIANT



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Cyber Lime
CADRE	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
FOURCHE	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPOSANTS	
CINTRE	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
POIGNÉES	Stratus Lite 3.0
POTENCE	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
TIGE DE SELLE	Giant D-Fuse SLR, composite, -5/+15mm offset
SELLE	Giant Grit SL
PÉDALES	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
DÉRAILLEUR	
MANETTES DÉRAILLEUR	SRAM Force AXS E1, 2x12
DÉRAILLEUR AVANT	SRAM Force AXS D2
DÉRAILLEUR ARRIÈRE	SRAM Force AXS E1
FREINS	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
LEVIERS DE FREIN	SRAM Force AXS E1 hydraulic
CASSETTE	SRAM Force E1, 12-speed, 10x36
CHAÎNE	SRAM Force E1
PÉDALIER	SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant CXR 1 WheelSystem, [F] 35mm, [R] 35mm
MOYEURS	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
RAYONS	Sapim CX-Ray
PNEUS	CADEX GX, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GÉOMÉTRIE

CADRE	XS	S	M	ML	L
	SHORT LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT
Longueur de tube de selle (mm)	430	450	470	490	510
Angle de tube de selle	74,0°	73,5°	73,5°	73,0°	73,0°
Longueur du tube supérieur (mm)	540	550	560	575	585
Longueur du tube de direction (mm)	125	135	150	165	180
Angle du tube de direction	70,0°	71,0°	71,5°	72,0°	72,0°
Déport de fourche (mm)	50	50	50	50	50
Chasse (mm)	78 82	72 75	68 72	65 68	65 68
Empattement (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051
Longueur des bases (mm)	425 435	425 435	425 435	425 435	425 435
Hauteur du boîtier de pédalier (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616
Reach (mm)	381	381	387	391	397
Hauteur d'enjambement (mm)	724 731	740 747	757 764	774 780	791 797
Largeur de cintre (mm)	420	420	440	440	460
Longueur de potence (mm)	50	60	70	80	80
Longueur des manivelles (mm)	170	170	172,5	172,5	175

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.